

SPHERES

14" Smooth Acrylic

DESCRIPTION

LBS Plastics smooth spheres are designed for commercial and residential post top and pendant applications and are available with fitter neck, neckless and custom openings.

MATERIALS


- Acrylic UV resistant with continuous operating temperature up to 80°C. Maximum transmittance of 92% (clear). Acrylic spheres are available in clear, white, bronze or smoke.
- LD Acrylic UV resistant with continuous operating temperature up to 80°C and transmittance of 90% to 94% (application dependent).



LD ACRYLIC FROST SHOWN

FITTER NECK (F)	ITEM NO.	DIA (SPHERE)	ID (NECK)	OD (NECK)	MATERIAL	COLOR
	20014-CL-6F	14"	5.20"	5.91"	Acrylic	Clear
	20014-WH-6F	14"	5.20"	5.91"	Acrylic	White
	20014-BR-6F	14"	5.20"	5.91"	Acrylic	Bronze
0.D.	20014-SM-6F	14"	5.20"	5.91"	Acrylic	Smoke
	20014-LD-6F	14"	5.20"	5.91"	LD Acrylic	Frost
	-	•	•	•		·

NECKLESS (N)



ITEM NO.	DIA (SPHERE)	ID (NECK)	OD (NECK)	MATERIAL	COLOR
20014-CL-5N	14"	5.25"	N/A	Acrylic	Clear
20014-WH-5N	14"	5.25"	N/A	Acrylic	White
20014-BR-5N	14"	5.25"	N/A	Acrylic	Bronze
20014-SM-5N	14"	5.25"	N/A	Acrylic	Smoke
20014-LD-5N	14"	5.25"	N/A	LD Acrylic	Frost

CUSTOM (XX)	ITEM NO.	DIA (SPHERE)	MIN (OPENING)	MAX (OPENING)	MATERIAL	COLOR
	20014-CL-XX	14"	5.25"	9.25"	Acrylic	Clear
	20014-WH-XX	14"	5.25"	9.25"	Acrylic	White
CUSTOM OPENING	20014-BR-XX	14"	5.25"	9.25"	Acrylic	Bronze
See ACCESSORIES section for all optional attachments	20014-SM-XX	14"	5.25"	9.25"	Acrylic	Smoke
an optional attachments	20014-LD-XX	14"	5.25"	9.25"	LD Acrylic	Frost

OPTIONAL ACCESSORIES

Aluminum Neck Fitters



98007-A 98007.5-A



Plastic Neck Fitters



98008-PSPEC-WHT 98008-PSPEC-BLK

External Heat Shields



96005-BLK 96005-WHT

Internal Heat Shields



96104-A

Dimensions are nominal

