




# 16" Smooth 6" Lip Globe



| ITEM NO.    | DIA (SPHERE) | ID (NECK) | OD (NECK) | MATERIAL   | COLOR  |
|-------------|--------------|-----------|-----------|------------|--------|
| 20016-CL-6F | 16"          | 5.20"     | 5.91"     | Acrylic    | Clear  |
| 20016-WH-6F | 16"          | 5.20"     | 5.91"     | Acrylic    | White  |
| 20016-BR-6F | 16"          | 5.20"     | 5.91"     | Acrylic    | Bronze |
| 20016-SM-6F | 16"          | 5.20"     | 5.91"     | Acrylic    | Smoke  |
| 20016-LD-6F | 16"          | 5.20"     | 5.91"     | LD Acrylic | Frost  |

## MATERIALS

- **Acrylic** - UV resistant with continuous operating temperature up to 80°C. Maximum transmittance of 92% (clear). Acrylic streetlamps are available in clear, white, bronze or smoke.
- **LD Acrylic** - UV resistant with continuous operating temperature up to 80°C and transmittance of 90% to 94% (application dependent).



## MAXIMUM TEMPERATURES

- No warranty or guarantee is expressed or implied as only the user can determine the suitability of a product for his or her purpose.
- Maximum working temperature is 80° C for Acrylic and between 100° C and 125° C for Polycarbonates, depending on products chosen.
- Actual wattage ratings are influenced by many factors including Fixture Type, Bulb Location and Ambient Temperature.