


- o Available in LED & Incandescent
- o White Powder Coated Aluminum
- o Wall or Ceiling Mount
- o UL Listed for Wet Locations
- o Standard Pack QTY: 6

10.5" Square Flush Mount



EXAMPLE: 18191-13LED-120-30K

| STYLE # | LIGHT SOURCE | BODY/DIFFUSER | OPTIONS |
|------------|---|---|--|
| 181 | EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70*, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE, ENERGY STAR | 1-White ACRYLIC 9-Clear 6-Glare Reduced Frost Prismatic POLYCARBONATE 9P-Clear | M-Motion Sensor |
| | 13LED - 13W, 80 CRI >88 Lumens Per Watt** W-1140lm 3000K C-1280lm 4000K 14LED - 14W, 80 CRI >102 Lumens Per Watt** W-1430lm 3000K C-1500lm 4000K 22LED - 22W, 80 CRI >88 Lumens Per Watt** W-1950lm 3000K C-2130lm 4000K | | |
| | INCANDESCENT, MEDIUM BASE, 120V 2E26-2 X 40W Max | 1-White ACRYLIC 9-Clear 6-Glare Reduced Frost Prismatic POLYCARBONATE 9P-Clear | LED LAMP, 3 YEAR WARRANTY DIMMABLE, ENERGY STAR 9LEDA19-30K-A19/E26, 80CRI, 3000K 9LEDA19-40K-A19/E26, 80CRI, 4000K |

*DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST **ESTIMATED FROM LED SOURCE

90CRI OPTIONS AVAILABLE