



## 181 SENTINEL - 10.5''

- White Powder Coated Aluminum
- UL Listed for Wet Locations
- Ceiling or Wall Mount
- Mounting Hardware Included
- Includes Gasket



### EXAMPLE # 181-LE800W-WFS

STYLE #	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
181	<b>DEDICATED 120V LED</b>	W-White	ACRYLIC C-Clear F-Glare Reduced Frost Prismatic	<b>S-Security</b> Motion Sensor & Photocell Combo. 120V only. See page 16. <b>EB-Emergency Backup</b> See page 123.
	EOS LED 120V AC, 50/60 Hz, HPF, 50,000 HRS L70, AMBIENT OP TEMP -40°C TO +40°C, 5 YEAR WARRANTY, DIMMABLE			
	<b>LE800</b> - 13W, 80 CRI >88 Lumens Per Watt** <b>W-1140lm 3000K</b> <b>C-1280lm 4000K</b>			
	<b>LE1200</b> - 14W, 80 CRI >102 Lumens Per Watt** <b>W-1430lm 3000K</b> <b>C-1500lm 4000K</b>			
181	<b>MULTI-VOLT 120-277V LED</b>	W-White	ACRYLIC C-Clear F-Glare Reduced Frost Prismatic	<b>S-Security</b> Motion Sensor & Photocell Combo. See page 16.
	MULTI-VOLT LED 120-277V, 50/60 Hz, CONSTANT CURRENT AT 700mA, DRIVER UL CLASS 2, HPF, THERMALLY PROTECTED ARRAY, 50,000 HRS L70° AMBIENT OP TEMP -40°C TO +40°C, 3 YEAR WARRANTY			
181	<b>INCANDESCENT 120V</b>	W-White	ACRYLIC C-Clear F-Glare Reduced Frost Prismatic	<b>S-Security</b> Motion Sensor & Photocell Combo. 120V only. See page 16. <b>EB-Emergency Backup</b> See page 123. LED LAMP, 3 YEAR WARRANTY, DIMMABLE
	INCANDESCENT, MEDIUM BASE, 120V <b>I240-2 X 40W Max</b>			
181	<b>INCANDESCENT 120V</b>	W-White	ACRYLIC C-Clear F-Glare Reduced Frost Prismatic	<b>LWE-A19/E26, 90CRI, 3000K</b> <b>LCE-A19/E26, 80CRI, 4000K</b>
	INCANDESCENT, MEDIUM BASE, 120V <b>I240-2 X 40W Max</b>			

See page 122 for dimmer compatibility. Data per LM79/LM80/TM21 available upon request. \*\*Estimated from LED source. Fixtures available with custom packaging options, assembled or knocked down. MOQs apply. Specification subject to change without notice.