

PROJECT

TYPE

VOLTAGE

# OUTDOOR WALL FIXTURE 2085







Lens

eveled Lens

## SPECIFICATIONS

- Black or White
- Mounting Hardware Included
- Clear or Opal Acrylic Diffuser Options
- Wall Mount Only
- Minimum Starting Temp -20°F
- UL Listed for Wet Locations
- Composite Construction



### **GUIDE CODE: 208SC-WH**

### **OUTDOOR DECORATIVE MARLEX®**

Wave Lighting's 208S adds a welcoming look to any outdoor space. Wave Lighting's 208S is designed for wall applications and mounting hardware is included. Options include photocell.



## LED SOURCE OPTIONS

### LIGHTWAVE LED - LR/LT

- 120V, 50/60 Hz
- AC Driver-On-Board Array
- Estimated 50,000 Hrs  $L_{70}$
- Low Flicker (LT models)
- Surge Supression
- Dimmable (see compatible dimmer list)
- High Efficacy LED Light Source
- 3000K or 4000K CCT 80 or 90CRI
- 5 Year Warranty
- Energy Star

### E26 MEDIUM BASE - LE26

- 120V, 50/60Hz
- "Screw-In" Medium Base A19/E26 LED Lamp
- Estimated 15,000 Hrs L<sub>70</sub>
- Low Flicker (3K models)
- Dimmable (see compatible dimmer list)
- 3000K CCT 90CRI or 4000K CCT 80CRI
- 3 Year Warranty
- Energy Star

### CALL FOR PHOTOMETRIC INFORMATION

ITEM #	LENS	LIGHT SOURCE	сст	COLOR	OPTIONS
2085	ACRYLIC	E26 MEDIUM BASE	С-4К W-3К	BK-Black WH-White	PC-Photocell
	C-Clear Glacier B-Clear Beveled L-Opal Beveled	(1) 60W MAX Medium Base <b>LE26</b> -9.5W 800Im (E26 LED Lamp) + *			
		120V LIGHTWAVE LED			
		LR12-13W 1000lm 80CRI ★ LT12-12W 1040lm 90CRI			

+ Lamp included. ★Energy Star qualified product.