

	Produc	t Spec	
Category	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires		
Item Code	7633		
Stock Code	LED-FXSAL180/50K/DB/3S	PICTURE	AND THE PARTY OF T
Mounting	EA6/SB/SF/WM/Yoke Mount	1	
Housing Color	Dark Bronze		

Housing Color	Dark Bronze				
Electric Characteristics		Photometr	Photometric Characteristics		
Rated Wattage (W)	180	Lumen (lm)	22743		
Tested Wattage (W)	182.5	Efficacy (lm/w)	125		
Input Voltage (V)	100~277	CRI	>70		
Voltage Frequency (Hz)	50/60	CCT (K)	5000		
Input Current (A)	1.6	Beam Angle (∘)	Type 3		
Power Factor	>0.9	General Characteristics			
Replacement Wattage (W)	400~575	Operating Temperature	-40°F~140°F		
Surge protect level	12KV	Storage Temperature	-40°F~140°F		
Dimmable	1-10V	IP rating	IP65		
ГНД	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
	imensions		Suggested Accesory		
Weight (lbs.)	23.6	Photocell Sensor			
Height (in)	3	Motion Sensor			
Length (in)	23.2	EA6/SB/SF/Yoke Mount			
Width (in)	15	Wall Mount			
Mounting Height (ft)		Type 4, Type 5 Lens			
Cable Length (ft)	1.97	48	480V driver		
		ifications			
UL/ETL	ETL	LM79	√		
Energy Star		LM80	√		
DLC	V4.4 Premium	IES File	√		
CEC		FDA			
A8		NEMA			
FCC	V	Dimmer List			
		•			