

	Produc	t Spec	
Category	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires		
Item Code	7637		
Stock Code	LED-FXSAL240/50K/DB/3S	PICTURE	A STATE OF THE STA
Mounting	EA6/SB/SF/WM/Yoke Mount	1	
Housing Color	Dark Bronze		

Input Voltage (V) Voltage Frequency (Hz) Input Current (A) Power Factor Replacement Wattage (W) Surge protect level	240 243.2 100~277 50/60 2.1 >0.9 750~1000 12KV 1-10V <20%	Lumen (lm) Efficacy (lm/w) CRI CCT (K) Beam Angle (°) General Operating Temperature Storage Temperature IP rating Rated Life Warranty	30274 124 >70 4000 Type 3 Characteristics -40°F~140°F -40°F~140°F IP65 50000 hrs 5 years		
Rated Wattage (W) Tested Wattage (W) Input Voltage (V) Voltage Frequency (Hz) Input Current (A) Power Factor Replacement Wattage (W) Surge protect level Dimmable THD Product Dimension	240 243.2 100~277 50/60 2.1 >0.9 750~1000 12KV 1-10V <20%	Lumen (lm) Efficacy (lm/w) CRI CCT (K) Beam Angle (°) General Operating Temperature Storage Temperature IP rating Rated Life Warranty	30274 124 >70 4000 Type 3 Characteristics -40°F~140°F -40°F~140°F IP65 50000 hrs		
Tested Wattage (W) Input Voltage (V) Voltage Frequency (Hz) Input Current (A) Power Factor Replacement Wattage (W) Surge protect level Dimmable THD Product Dimension	100~277 50/60 2.1 >0.9 750~1000 12KV 1-10V <20%	Efficacy (lm/w) CRI CCT (K) Beam Angle (°) General Operating Temperature Storage Temperature IP rating Rated Life Warranty	>70 4000 Type 3 Characteristics -40°F~140°F -40°F~140°F IP65 50000 hrs		
Input Voltage (V) Voltage Frequency (Hz) Input Current (A) Power Factor Replacement Wattage (W) Surge protect level Dimmable THD Product Dimension	50/60 2.1 >0.9 750~1000 12KV 1-10V <20%	CRI CCT (K) Beam Angle (°) General Operating Temperature Storage Temperature IP rating Rated Life Warranty	4000 Type 3 Characteristics -40°F~140°F -40°F~140°F IP65 50000 hrs		
Voltage Frequency (Hz) Input Current (A) Power Factor Replacement Wattage (W) Surge protect level Dimmable THD Product Dimension	2.1 >0.9 750~1000 12KV 1-10V <20%	Beam Angle (°) General Operating Temperature Storage Temperature IP rating Rated Life Warranty	Type 3 Characteristics -40°F~140°F -40°F~140°F IP65 50000 hrs		
Input Current (A) Power Factor Replacement Wattage (W) Surge protect level Dimmable THD Product Dimension	>0.9 750~1000 12KV 1-10V <20%	General Operating Temperature Storage Temperature IP rating Rated Life Warranty	Characteristics -40°F~140°F -40°F~140°F IP65 50000 hrs		
Power Factor Replacement Wattage (W) Surge protect level Dimmable THD Product Dimension	750~1000 12KV 1-10V <20%	General Operating Temperature Storage Temperature IP rating Rated Life Warranty	Characteristics -40°F~140°F -40°F~140°F IP65 50000 hrs		
Surge protect level Dimmable THD Product Dimension	12KV 1-10V <20%	Storage Temperature IP rating Rated Life Warranty	-40°F~140°F IP65 50000 hrs		
Surge protect level Dimmable THD Product Dimension	1-10V <20%	IP rating Rated Life Warranty	IP65 50000 hrs		
Product Dimension	<20%	Rated Life Warranty	50000 hrs		
Product Dimension	ns	Warranty			
	ns				
		Sugges			
		Sugges			
		Suggos			
Weight (lbs.)			Suggested Accesory		
	24.7		ocell Sensor		
Height (in)	3	Mot	tion Sensor		
Length (in)	23.2	EA6/SB/	/SF/Yoke Mount		
Width (in)	15	W	all Mount		
Mounting Height (ft)		Type 4	ł, Type 5 Lens		
Cable Length (ft)	1.97		30V driver		
5 12					
	-		-		
	Qua	lifications			
UL/ETL	ETL	LM79	٧		
Energy Star		LM80	٧		
DLC	V4.4 Premium	IES File	٧		
CEC		FDA	<u>.</u>		
JA8		NEMA			
FCC	٧	Dimmer List			
RoHS	٧				