



| | Produc | t Spec | |
|---------------|---|---------|--|
| Category | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires | | |
| Item Code | 7638 | PICTURE | |
| Stock Code | LED-FXSAL240/40K/WH/3S | | |
| Mounting | EA6/SB/SF/WM/Yoke Mount | 1 | |
| Housing Color | White | | |

| Housing Color | White | | | | |
|-------------------------|---------------|-------------------------|----------------------|--|--|
| Electric Cha | aracteristics | Photometr | ric Characteristics | | |
| Rated Wattage (W) | 240 | Lumen (lm) | 29794 | | |
| Tested Wattage (W) | 242.5 | Efficacy (lm/w) | 123 | | |
| Input Voltage (V) | 100~277 | CRI | >70 | | |
| Voltage Frequency (Hz) | 50/60 | ССТ (К) | 4000 | | |
| Input Current (A) | 2.1 | Beam Angle (∘) | Туре 3 | | |
| Power Factor | >0.9 | General Characteristics | | | |
| Replacement Wattage (W) | 750~1000 | Operating Temperature | -40°F~140°F | | |
| Surge protect level | 12KV | Storage Temperature | -40°F~140°F | | |
| Dimmable | 1-10V | IP rating | IP65 | | |
| THD | <20% | Rated Life | 50000 hrs | | |
| | | Warranty | 5 years | | |
| | | | | | |
| | | ' | | | |
| Product Dimensions | | Sugges | Suggested Accesory | | |
| Weight (lbs.) | 24.7 | Phot | Photocell Sensor | | |
| Height (in) | 3 | Mot | Motion Sensor | | |
| Length (in) | 23.2 | EA6/SB/ | EA6/SB/SF/Yoke Mount | | |
| Width (in) | 15 | W | Wall Mount | | |
| Mounting Height (ft) | | Type 4 | Type 4, Type 5 Lens | | |
| Cable Length (ft) | 1.97 | 48 | 30V driver | | |
| | | | | | |
| • | | ' | | | |
| | Qua | lifications | | | |
| UL/ETL | ETL | LM79 | ٧ | | |
| Energy Star | | LM80 | ٧ | | |
| DLC | V4.4 Premium | IES File | ٧ | | |
| CEC | | FDA | | | |
| JA8 | | NEMA | | | |
| FCC | ٧ | Dimmer List | | | |
| RoHS | ٧ | | | | |
| | | | | | |