

	Produc	t Spec	
Category	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires		
Item Code	7641		
Stock Code	LED-FXSAL360/50K/DB/3S	PICTURE	
Mounting	EA6/SB/SF/WM/Yoke Mount		
Housing Color	Dark Bronze		

Electric Characteristics		Photometric Characteristics		
Rated Wattage (W)	360	Lumen (lm)	45878	
Γested Wattage (W)	367.7	Efficacy (lm/w)	125	
nput Voltage (V)	100~277	CRI	>70	
Voltage Frequency (Hz)	50/60	сст (к)	5000	
nput Current (A)	3.1	Beam Angle (°)	Type 3	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)	1000~1500	Operating Temperature	-40°F~140°F	
Surge protect level	12KV	Storage Temperature	-40°F~140°F	
Dimmable	1-10V	IP rating	IP65	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
Dwoduct	Dimensions	Suggeste	d Agggowy	
	24.88		d Accesory ell Sensor	
Weight (lbs.)	3			
Height (in)		Motion Sensor		
Length (in)	23.2	EA6/SB/SF/Yoke Mount		
Width (in)	15	Wall Mount		
Mounting Height (ft)	4.05	Type 4, Type 5 Lens		
Cable Length (ft)	1.97	480V	driver	
	Oual	ifications		
	ETL	LM79	٧	
JL/ETL				
		LM80	٧	
Energy Star	V4.4 Premium		√ √	
Energy Star DLC	V4.4 Premium	LM80		
Energy Star DLC CEC	V4.4 Premium	LM80 IES File		
UL/ETL Energy Star DLC CEC JA8 FCC	V4.4 Premium	LM80 IES File FDA		