Noturaled[®] Product Engineering Spec

	Product Spec					
Category	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires					
Item Code	7643					
Stock Code	LED-FXSAL360/50K/WH/3S					
Mounting	EA6/SB/SF/WM/Yoke Mount					
Housing Color	White					

Electric Cha	racteristics	Photometr	Photometric Characteristics		
Rated Wattage (W)	360	Lumen (lm)	45878		
Tested Wattage (W)	367.7	Efficacy (lm/w)	125		
Input Voltage (V)	100~277	CRI	>70		
Voltage Frequency (Hz)	quency (Hz) 50/60		5000		
Input Current (A)	3.1	Beam Angle (°)	Туре 3		
Power Factor	>0.9	General	General Characteristics		
Replacement Wattage (W)	1000~1500	Operating Temperature	Operating Temperature -40°F~140°F		
Surge protect level	12KV	Storage Temperature	-40°F~140°F		
Dimmable	1-10V	IP rating	IP65		
THD	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
Product D	imensions	Sugges	Suggested Accesory		
Weight (lbs.) 24.88		Phot	Photocell Sensor		
Height (in)	3	Mot	tion Sensor		
Length (in)	23.2	EA6/SB/	/SF/Yoke Mount		
Width (in)	15	W	all Mount		
Mounting Height (ft)		Type 4, Type 5 Lens			
Cable Length (ft)1.97		480V driver			
	Qua	lifications			
UL/ETL	ETL	LM79	V		
Energy Star		LM80	V		
DLC	V4.4 Premium	IES File	V		
CEC		FDA			
JA8		NEMA			
		Dimmer List			
FCC	V	Dimmer List			