


# natural<sup>led</sup>®

## Product Engineering Spec


Product Spec			
Category	Slim Area Light	PICTURE	
Order #	7751		
Item #	LED-FXSAL360/30K/WH/3S		
Mounting	EA6/SB/SF/Yoke Mount		
Housing Color	White		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	360	Lumen (lm)	44796
Tested Wattage (W)	366	Efficacy (lm/w)	122
Input Voltage (V)	100~277	CRI	70
Voltage Frequency (Hz)	50/60	CCT (K)	3000
Input Current (A)	3.1	Beam Angle (°)	Type 3
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	-	Operating Temperature	-40°F~140°F
Surge protect level	12KV	Storage Temperature	-40°F~140°F
Dimmable	1-10V	IP rating	IP65
THD	<20%	Rated Life	50000 hrs
		Warranty	5 years

Product Dimensions		Suggested Accessory	
Weight (lbs.)		Photo Sensor	
Height (in)	3	Motion Sensor	
Length (in)	23.2	SF/SB/EA6/Yoke Mount	
Width (in)	15		
Mounting Height (ft)			
Cable Length (ft)			

Qualifications			
UL/ETL	ETL	LM79	√
Energy Star		LM80	√
DLC	DLC V4.3 Premium	IES File	√
CEC		FDA	
JA8		NEMA	
FCC	√	Dimmer List	
RoHS	√		

Comments: