

Sunlite 81041 12-Inch LED Cylinder Outdoor Up & Down Wall Sconce, Clear Acrylic Cylinder, 10W, 600 Lmns, Color Selectable 30K/40K/50K, Dimmable, ETL Listed, Black, For Residential & Commercial Use

Seedy

DESCRIPTION:

Sunlite's LED 12-Inch LED Outdoor Up & Down Wall Sconce provides a unique experience for your outdoor lighting. These fixtures allow you to choose the color temperature at the installation time. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight, depending on your preference, using a switch located within the fixture. These wall sconces have a long lifespan of 50,000 hours and are energy-efficient, using only 10W instead of traditional lighting options that require 60W to provide the same coverage. light output can be changed to change the ambiance from brilliant ambient lighting to warm and cozy accent lighting, when connected to a compatible LED dimmer. ETL Listed for wet location installation. Ideal for Porches, Garage, Entryway and more. Fixture measures 4.75" W x 12" H x 4" D.

FEATURES:

- UNIQUE DESIGN Contemporary matte black aluminum frame holds a unique raindrop clear acrylic cylinder. Illuminates both up and down lighting to make any exterior wall shine with hidden LEDs refract through the shimmering in the panel creating a brilliant decorative effect. Designed for residential or commercial installations.
- COLOR SELECTABLE These fixtures allow you to choose the color temperature at the installation time. Select 3000K Warm White, 4000K Cool White, or 5000K Daylight, depending on your preference, using a switch located within the fixture.
- LONG LIFE SPAN These wall sconces have a long lifespan of 50,000 hours and are energy-efficient, using only 10W instead of traditional lighting options that require 60W to provide the same coverage.
- DIMMABLE The light output can be changed to change the ambiance from brilliant ambient lighting to warm and cozy accent lighting, when connected to a compatible LED dimmer.





SPECIFICATIONS:

General Characteristics

Average Rated Hours

Finish

Average Life Span Years

Dimmable

Dimming Percentage

Material

Lens Material

Lens Finish

Electrical Characteristics

Watts 10

Volts 120 2835 LED Chip Manufacturer

Power Factor 0.9

Temperature -4°F - 113°F

50000

46

Yes

10-100%

Aluminum

Clear Seedy

Glass

600

80

<30%

CCT Selectable

30K/40K/50K

Textured Black

Light Characteristics

Lumens Brightness

Color Rendering Index CRI

Emitted Color

Color Temperature Kelvin

Flicker

Fixture Characteristics

Wall Mounting

LED Fixture Technology Use Location

Outdoor

Additional Features

Safety Rating Mark ETL Listed - Wet Location

Product Dimensions

Item Dimension (in) Package Dimension (in)

Package Weight (lb)

Product Data

Case Unit Rate

Item UPC

Warranty Years

(W) 4.75 (H) 12 (D) 4 (W) 6.3 (H) 13.3 (D) 7.8

7.33

653703810416

5