

**Sunlite 85261 LED 8-Foot Linear
Vaporproof Fixture, Power Selectable
72W/80W/100W, Color Selectable
35K/40K/50K, 13500 Lumens, Dimmable,
120-277 Volts, ETL Listed, For
Residential & Commercial Use**



DESCRIPTION:

Discover the ultimate lighting solution with Sunlite's 8-foot LED vaporproof fixture, offering energy efficiency and maintenance-free convenience. These fixtures provide instant full brightness with no warmup time, outperforming traditional fluorescent options. Designed with a durable frosted polycarbonate lens and robust plastic body, they ensure even light distribution and a reliable 50,000-hour lifespan with no bulbs to replace. Customize your lighting experience by selecting from 3500K, 4000K, or 5000K color temperatures and selectable wattages of 72W/80W/100W, providing a brilliant output of up to 13500 lumens. Adjust the lighting output using an LED-compatible dimmer switch (0-10V) and enjoy a wide 125-degree beam angle to create the perfect mood. ETL Listed for wet locations and compatible with 120-277V service, these fixtures are designed for safety and versatility. Easy to install with included mounting hardware and instructions. For use in Car Washes, Parking Garages, Workshops, Residential and Commercial. Fixture dimensions are 94.5" L x 4.33" W x 4.13" H.

FEATURES:

- **LED TECHNOLOGY** - These 8-foot LED vaporproof linear fixtures are an energy efficient and maintenance free solution to your lighting needs. Unlike fluorescent fixtures, LEDs are instant on at full brightness with no warmup time. This dimmable fixture features a durable frosted polycarbonate lens and a durable plastic body for even light distribution.
- **ENERGY EFFICIENT** - Estimated annual energy costs of \$3.61/\$4.82/\$6.2 (Based on 3 hours/day at \$0.11/kWh). 50,000-hour life span with no bulbs to replace provides years of reliable service while saving time and maintenance costs.
- **COLOR & POWER SELECTABLE** - This fixture allows you to choose the color temperature and wattage at any time. Select 3500K, 4000K or even 5000K depending on your preference using a switch located inside of the fixture. Take control of the light emitted with its selectable wattage of 72W/80W/100W with a bright lumen output of 9720/10800/13500 lumens depending on wattage setting.
- **DIMMABLE** - The lighting output can be changed when connected to an LED-compatible dimmer switch (0-10v), with a beam angle of 125 degrees, allowing it to adapt to any lighting to suit your needs.
- **ETL LISTED**- This fixture is ETL Listed for wet location. IP66 Rated. Operates on 120-277-volt service. Mounting hardware and installation instruction included. For use in Car Washes, Parking Garages, Workshops, Residential and Commercial. Fixture dimensions are 94.5" L x 4.33" W x 4.13" H.

SPECIFICATIONS:

General Characteristics

Bulb Shape	Integrated LED
Finish	Gray
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	10-100%
Lens Finish	White
Bulb Type	Integrated

Product Dimensions

Size	8'
Item Dimension (in)	(W) 96 (H) 4.13 (D) 4.33

Product Data

Case Unit Rate	1
Item UPC	653703852614
Warranty Years	5

Electrical Characteristics

Watts	72/80/100
Volts	120-277
LED Chip Manufacturer	Lumileds
Power Factor	0.9
Temperature	-4°F - 113°F

Light Characteristics

Lumens Brightness	9800/11000/13500
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	35K/40K/50K
Flicker	<30%

Fixture Characteristics

Shape	Linear
Number of Lights	1
Mounting	Surface
Motion Sensor	Yes
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	ETL Listed - Wet Location
Safety Rated For USA	Yes
DLC	Yes
DLC Classification	Standard
Rohs Compliant	Yes
Mercury Free	Yes