

Sunlite 4-Foot Linear Strip Light Wraparound Light Fixture, Power Selectable 32W/40W/48W, 5568 Lumens, Color Selectable 35K/40K/50K, Dimmable, 120 Degree Beam Angle, 120-277V, UL Listed

DESCRIPTION:

Upgrade your lighting to the eco-friendly Sunlite 4-Foot Linear Strip Light Wraparound Fixture. These fixtures allow you to choose the color temperature at the time of installation. Select 3500K Neutral White, 4000K Cool White, or 5000K Daylight depending on your preference, using a switch located inside the fixture. A second switch allows you to select between wattage for different lumen outputs. Choose 32 watts, 40 watts, or 48 watts. This dimmable fixture long life provides 50,000 hours of maintenance-free service LED technology. Estimated annual energy costs of \$3.85/\$4.82/\$5.78 (Based on 3 Hrs/Day at \$0.11/kWh). UL Listed for safety and quality. Designed for damp location use. Great for residential and commercial applications on 120–277-volt service. Fixture Dimension: 47.6" L x 5.31" W x 2.14" H.

FEATURES:

- **MODERN DESIGN** – This fixture is made with white steel body with acrylic diffuser lens with integrated LED. Fixture body has multiple knockouts for convenient installation. This LED Lighting fixture does not contain any mercury or glass.
- **COLOR AND POWER SELECTABLE** – These fixtures allow you to choose the color temperature at the time of installation. Select 3500K Neutral White, 4000K Cool White, or 5000K Daylight depending on your preference, using a switch located inside the fixture. A second switch allows you to select between wattage for different lumen outputs. Choose 32W and 3500K color for 3936 lumens, 40W and 3500K color for 4800 lumens, 48W and 3500K color for 5520 lumens, 32W and 4000K for 3968 lumens, 40W and 4000K color for 4840 lumens, 48W and 4000K color for 5568 lumens, 32W and 5000K color for 4000 lumens, 40W and 5000K color for 4880 lumens, 48W and 5000K color for 5616 lumens.
- **ENERGY EFFICIENT** – This dimmable fixture long life provides 50,000 hours of maintenance-free service LED technology. Estimated annual energy costs of \$3.85/\$4.82/\$5.78 (Based on 3 Hrs/Day at \$0.11/kWh). Benefit from significant energy savings over time.
- **DIMMABLE** – The lighting output can be changed when connected to an LED-compatible dimmer switch (0-10v) allowing it to adapt to any lighting to suit the mood.
- **UL LISTED** – UL Listed for safety and quality. Designed for damp location use. Great for residential and commercial applications on 120–277-volt service. Fixture Dimension: 47.6" L x 5.31" W x 2.14" H.

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	White
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	10-100%
Material	Steel
Lens Material	PMMA
Lens Finish	White
Application	Commercial

Electrical Characteristics

Watts	32/40/48
Volts	120-277
LED Chip Manufacturer	BLX
Temperature	-4°F - 122°F

Light Characteristics

Lumens Brightness	3680/4600/5520
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	35K/40K/50K
Beam Angle	110°

Fixture Characteristics

Style	Wraparound
Mounting	Surface
Fixture Technology	LED
Use Location	Indoor

Additional Features

Safety Rating Mark	UL Listed - Damp Location
DLC	Yes
Mercury Free	Yes

Product Dimensions

Size	48"
Item Dimension (in)	(W) 5.7 (H) 2.4 (D) 48.5
Item Weight (lb)	4.95

Product Data

Case Unit Rate	4
Item UPC	653703852980
Warranty Years	5