

Sunlite 87808 4" LED Commercial Recessed Round Downlight Fixture, Power Selectable 9W/13W/18W, 2000 Lmns, CCT Switch 27K/30K/35K/40K/50K, 90 CRI, Energy Star, Dimmable, Title-24 Compliant, ETL Listed

DESCRIPTION:

Sunlite's LED Commercial Recessed Round Downlight Fixture is an exceptional lighting solution for businesses seeking to optimize their commercial design. These fixtures allow you to choose the color temperature at the time of installation. Select 2700K Soft White. 3000K Warm White. 3500K Neutral White. 4000K Cool White, or 5000K Daylight depending on your preference using a switch located on the back of the fixture. A second switch allows you to select between wattage for different lumen outputs. Multi-wattage at 9-Watt for 1000 lumens, 13-Watt for 1500 lumens and 18-Watt for 2000 lumens. LED technology means 50,000 hours of maintenancefree service. No ladders to climb or difficult-to-reach bulbs to replace. Estimated annual energy costs of \$1.08/\$1.57/\$2.17 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. This fixture is ETL Listed for damp Location Installation. It also meets the necessary ratings for the USA, ensuring it is a reliable and safe choice for outdoor lighting needs. NEC rated BX cable connection and attached safety cable. Title-24 and RoHS Compliant. 120-347 multi-volts. Ideal for Retail, Hotels, Offices and more. Fixture Dimensions 4.02" H x 5.91" D.

FEATURES:

- COMMERCIAL DESIGN Designed with easy, canless installation with clamp system, instant-start LED chips and IC-rated for direct contact with insulation, it offers robust lighting and safety features that simplify setup, reduce cost and ensure a well-lit environment.
- COLOR AND POWER SELECTABLE These fixtures allow you to choose the color temperature at the time of installation. Select 2700K Soft White, 3000K Warm White, 3500K Neutral White, 4000K Cool White, or 5000K Daylight depending on your preference using a switch located on the back of the fixture. A second switch allows you to select between wattage for different lumen outputs. Multi-wattage at 9-Watt for 1000 lumens, 13-Watt for 1500 lumens and

nese fixtures can be dimmed when attached (0-10V) dimming control. Range is 100-legrees beam angle. High color rendering nces your surroundings appearance and e color perception.

DIENT - LED technology means 50,000 nance-free service. No ladders to climb or

difficult-to-reach bulbs to replace. Estimated annual energy





SPECIFICATIONS:

General Characteristics

Average Rated Hours **Finish** White 46 Average Life Span Years

Dimmable

Dimming Type **Dimming Percentage**

Material Lens Material Lens Finish

50000

Yes

0-10V Low Voltage

10-100% **Aluminum** Plastic White

Product Dimensions

Size (W) 5.91 (H) 4.02 (D) 5.91 Item Dimension (in)

Product Data

Case Unit Rate 6 Pack Size 1

Item UPC 653703878089

Warranty Years 5

Electrical Characteristics

Watts 9/13/18 **Volts** 120-347 LED Chip Manufacturer 2835 **Power Factor** 0.9 -4°F - 104°F **Temperature**

Light Characteristics

Lumens Brightness 1000/1500/2000

Color Rendering Index CRI 90

Emitted Color CCT Selectable

Color Temperature Kelvin 27K/30K/35K/40K/50K

Beam Angle 90°

Fixture Characteristics

Shape Round **Number of Lights** 1

Mounting Recessed Yes IC Rating LED Fixture Technology Use Location Indoor

Additional Features

Safety Rating Mark ETL - Damp Location

Yes Safety Rated For USA **Energy Star** Yes 2473608 **Energy Star Number Rohs Compliant** Yes Mercury Free Yes



ACCESSORIES:

Catalog # **88154-SU**