

14" Decorative Flush Mount Ceiling Light Fixture

Standard

DESCRIPTION:

21 Watts, 1500 Lumens, Color Selectable 27K/30K/35K/40K/50K, Dimmable, 90 CRI, Energy Star, 120 Volts. ETL Listed. Title-24 Compliant

FEATURES:

- TRADITIONAL DESIGN This decorative ceiling fixture is a simple, economical solution for your indoor lighting needs. It features a brushed nickel finish and adds a touch of elegance to any room's decor.
- COLOR SELECTABLE These dimmable fixtures put out a bright 1500 lumens and allow you to choose the color temperature at the time of installation. Select 2700K, 3000K, 3500K, 4000K or even 5000K depending on your preference using a switch located within the fixture.
- ENERGY EFFICIENT Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. Estimated annual energy costs of \$2.53 (Based on 3 Hrs/Day at \$0.11/kWh). Built-in long-life LED technology means 50,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace.
- DIMMABLE The fixture can be dimmed (10-100%) when installed with a Forward Phase (Triac or Incandescent) Dimmer. High color rendering at 90 CRI.
- ETL Listed ETL Listed for damp location installation.

 These ceiling fixtures can be easily mounted to a standard junction box. Hardware and instructions for mounting are included. Title-24 and RoHS Compliant. Fixture measures 3.75" H x 13.875" D.





14



SPECIFICATIONS:

General Characteristics

Average Rated Hours

Finish

Average Life Span Years

Dimmable

Dimming Type

Dimming Percentage

Material Lens Material Lens Finish

Application

50000

Brushed Nickel

46 Yes

Forward Phase (Triac or

Incandescent)

10-100% Steel Acrylic White Residential **Product Dimensions**

 Size
 14"

 MOL (in)
 3.75

Diameter (in)

Product Data

Case Unit Rate 6

Item UPC 653703878133

Warranty Years 5

Electrical Characteristics

 Watts
 21

 Volts
 120

LED Chip Manufacturer SAMSUNG 2835

Power Factor 0.7

Temperature -4°F - 104°F

Light Characteristics

Lumens Brightness 1500
Color Rendering Index CRI 90

Emitted Color CCT Selectable

Color Temperature Kelvin 27K/30K/35K/40K/50K

Beam Angle 120°

Fixture Characteristics

ShapeRoundMountingSurfaceFixture TechnologyLEDUse LocationIndoor

Additional Features

Safety Rating Mark ETL - Damp Location

Safety Rated For CanadaYesSafety Rated For USAYesRohs CompliantYes