

Sunlite 88144 LED Outdoor Vapor Tight Light Fixture, 21 Watts, 2562 Lumens, Color Selectable 30K/40K/50K, Ceiling/Wall Mount, 120-277V, UL Listed, Dimmable, Grey, For Residential & Commercial Use

DESCRIPTION:

This durable outdoor light tight fixture from Sunlite features grey vapor-tight housing, ensuring longevity and minimal maintenance. With a 50,000-hour lifespan, it consumes only 21 watts while delivering 2562 lumens. Designed to be ceiling or wall mounted to a standard junction box or direct surface mounted and wired through any of the 4 conduit openings on the base. The dimmable fixture offers adjustable color temperature and brightness when connected to an LED-compatible dimmer. UL listed for wet locations and IP65 rated, it guarantees safety and reliability. Dimensions: 4.96" W x 12.6" H x 4.96" D.

FEATURES:

- **WEATHERPROOF CONSTRUCTION** – Made with robust, grey vapor-tight housing, this light fixture is designed to withstand harsh outdoor conditions, ensuring long-lasting performance and minimal maintenance.
- **ENERGY EFFICIENT** – With a remarkable lifespan of 50,000 hours, this fixture consumes only 21 watts of power while delivering a bright output of 2562 lumens, reducing energy consumption and saving on utility bills with 120-277 volts.
- **CEILING OR WALL MOUNT** - Designed to be ceiling or wall mounted to a standard junction box or direct surface mounted and wired through any of the 4 conduit openings on the base.
- **COLOR SELECTABLE & DIMMABLE** - These dimmable fixtures put out a bright 2562 lumen and allow you to choose the color temperature at the time of installation. Select 3000K, 4000K or even 5000K depending on your preference, using a switch located within the fixture. This fixture can also be adjusted between 10% and 100% when connected to a 0-10V low voltage dimmer.
- **UL LISTED** – UL listed for wet location, ensuring it meets strict safety and performance standards for your peace of mind. IP65 rating. Ideal for residential areas, commercial buildings, parking lots, walkways, and other outdoor settings where reliable, energy-efficient lighting is needed. Fixture Dimension: 4.96" W x 12.6" H x 4.96" D.

SPECIFICATIONS:

General Characteristics

Average Rated Hours	50000
Finish	Gray
Average Life Span Years	46
Dimmable	Yes
Dimming Type	0-10V Low Voltage
Dimming Percentage	0-100%
Material	Aluminum
Lens Material	Glass
Lens Finish	Frosted
Application	Outdoor

Electrical Characteristics

Watts	21
Volts	120-277
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	-4°F - 113°F

Light Characteristics

Lumens Brightness	2560
Color Rendering Index CRI	80
Emitted Color	CCT Selectable
Color Temperature Kelvin	30K/40K/50K
Beam Angle	160°

Fixture Characteristics

Mounting	Surface
Fixture Technology	LED
Use Location	Outdoor

Additional Features

Safety Rating Mark	UL Listed - Wet Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Classification	Standard
Rohs Compliant	Yes
Mercury Free	Yes
CE Certified	Yes

Product Dimensions

Item Dimension (in)	(W) 4.96 (H) 4.96 (D) 12.6
---------------------	----------------------------

Product Data

Case Unit Rate	6
Item UPC	653703881447
Warranty Years	5