

## Sunlite 88907-SU LED Dual-Head Round Wall Mount Flood Light Fixture With Motion Sensor, 20 Watts, 120 Volts, 1800 Lumen Output, Round Lights, IP65 Rated, ETL Listed, 50K - Super White, Black Finish

Security

### DESCRIPTION:

Sunlite LED Round Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Dual heads can be adjusted individually to optimize coverage area. Built-in motion sensor activates lights when movement is detected. With a bright 1800 lumen output at 5000K Super White color temperature they are an energy efficient solution for your lighting needs. Each fixture uses only 20 watts with a low estimated yearly energy cost of \$2.41. (Based on 3 hours/day use at \$0.11/kWh) Ideal for security and entryway lighting in residential or commercial locations. Long life, LED technology built-in means no bulbs to replace and up to 35,000 hours of maintenance-free service. ETL Listed for wet location installation and IP65 rated.

### FEATURES:

- **LED TECHNOLOGY** - Sunlite LED Round Wall Mount Floodlight fixtures provide ample illumination for all outdoor spaces. Each fixture contains 48 high output LEDs and dual heads that can be adjusted individually to optimize coverage area.
- **ENERGY EFFICIENT** - Each fixture uses only 20 watts of energy. Estimated yearly energy cost is a low \$2.41. (Based on 3 hours/day use at \$0.11/kWh) With a 35,000 hour lifespan these fixtures will provide significant savings in electricity over their lifetime and require no maintenance.
- **BUILT-IN MOTION SENSOR** - Built-in motion sensor activates lights when movement is detected.
- **SECURITY AND ENTRYWAY LIGHTING** - Each fixture contains 48 LEDs and gives off a bright 1800 lumen output with 5000K Super White color temperature. Ideal for security and entryway lighting in residential or commercial installations.
- **ETL LISTED** - These fixtures are ETL Listed for wet location installation. They operate on 120 volt service.



## SPECIFICATIONS:

### General Characteristics

<b>Average Rated Hours</b>	35000
<b>Finish</b>	Black
<b>Average Life Span Years</b>	32
<b>Dimmable</b>	No
<b>Material</b>	Aluminum & Plastic
<b>Lens Material</b>	Polycarbonate
<b>Lens Finish</b>	Clear

### Electrical Characteristics

<b>Watts</b>	20
<b>Volts</b>	120
<b>LED Chip Manufacturer</b>	SMD2835
<b>Power Factor</b>	0.9
<b>Temperature</b>	.-20°C-45°C

### Light Characteristics

<b>Lumens Brightness</b>	1800
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Super White
<b>Color Temperature Kelvin</b>	5000K
<b>Flicker</b>	60°

### Fixture Characteristics

<b>Shape</b>	Rectangular
<b>Number of Lights</b>	2
<b>Mounting</b>	Wall
<b>Fixture Technology</b>	LED
<b>Use Location</b>	Outdoor

### Additional Features

<b>Safety Rating Mark</b>	ETL Listed - Wet Location
<b>Safety Rated For Canada</b>	Yes
<b>Safety Rated For USA</b>	Yes

### Product Dimensions

<b>Item Dimension (in)</b>	(W) 6.34 (H) 9.25 (D) 7.6
<b>Package Dimension (in)</b>	(W) 9 (H) 8.2 (D) 6.9
<b>Package Weight (lb)</b>	1.950
<b>Canopy Width (in)</b>	4.2
<b>Canopy Height (in)</b>	1.5

### Product Data

<b>Case Unit Rate</b>	6
<b>Item UPC</b>	653703889078
<b>Warranty Years</b>	2