Noturaled[®] Product Engineering Spec

	Prod	ict Spec	-		
Category	LED Cut Off Wallpack				
Item Code	9208				
Stock Code	LED-FXCWP60/40K/BZ	PICTURE	*		
Mounting	Wall Mount			•	
Housing Color	Bronze				
	•				
	c Characteristics			ic Characteristics	
Rated Wattage (W)	60		Lumen (lm)	8,347	
Fested Wattage (W)	61.421	Efficacy (lm/w)		120	
nput Voltage (V)	100~277	CRI		>70	
/oltage Frequency (Hz)	50/60	CCT (K)		4000	
nput Current (A)	0.5154		Beam Angle (°)	Forward Throw	
Power Factor	>0.9		General Characteristics		
Replacement Wattage (W)	250 ~ 400	Operatir	g Temperature	-40°F~122°F	
Surge protect level	4KV	Storag	ge Temperature	-40°F~176°F	
Dimmable	1-10V		IP rating	IP65	
ГНД	<20%		Rated Life	50000 hrs	
			Warranty	5 years	
	•	•			
Product Dimensions			Suggested Accessory		
Prod	uct Dimensions		Suggest	ted Accessory	
Prod Weight (lbs.)	uct Dimensions 7.05			t ed Accessory hotocell	
			Р		
Weight (lbs.)	7.05		Р	hotocell	
Weight (lbs.) Height (in)	7.05 9.25		Р	hotocell	
Weight (lbs.) Height (in) Length (in)	7.05 9.25 14.17		Р	hotocell	
Weight (lbs.) Height (in) Length (in) Width (in)	7.05 9.25 14.17		Р	hotocell	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft)	7.05 9.25 14.17		Р	hotocell	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft)	7.05 9.25 14.17		Р	hotocell	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft)	7.05 9.25 14.17 6.54	ications	Р	hotocell	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft)	7.05 9.25 14.17 6.54	ications	Р	hotocell	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) JL/ETL	7.05 9.25 14.17 6.54 Quali	ications	P	hotocell M driver	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) JL/ETL Energy Star	7.05 9.25 14.17 6.54 Quali	ications	Р Е 	hotocell M driver	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	7.05 9.25 14.17 6.54 Quali	ications	P E LM79 LM80 IES File	hotocell M driver 	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	7.05 9.25 14.17 6.54 Quali	ications	P E 	hotocell M driver 	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	7.05 9.25 14.17 6.54 Quali	ications	P E LM79 LM80 IES File FDA NEMA	hotocell M driver 	
Weight (lbs.) Height (in) Length (in) Width (in) Mounting Height (ft)	7.05 9.25 14.17 6.54 Quali UL/cUL V5.1 Premiun	Image: Control of the second	P E LM79 LM80 IES File FDA	hotocell M driver 	