

	Prod	uct Spec	
Category	Slim Canopy		Aug.
Item Code	9212	7	
Stock Code	LED-FXSCM100/50K/BK	PICTURE	
Mounting	Ceiling		
Housing Color	Black		

Housing Color	Black				
Electric	Characteristics	Photometric	Characteristics		
Rated Wattage (W)	100	Lumen (lm)	12516		
Tested Wattage (W)	99.46	Efficacy (lm/w)	126		
Input Voltage (V)	120~277	CRI	70		
Voltage Frequency (Hz)	50/60	CCT (K)	5000		
Input Current (A)	1.05	Beam Angle (∘)	Parking Garage		
Power Factor	>0.9	General C	General Characteristics		
Replacement Wattage (W)	-	Operating Temperature	-22°F~131°F		
Surge protect level	4KV	Storage Temperature	-40°F~140°F		
Dimmable	1-10V	IP rating	IP65		
THD	<20%	Rated Life	50000 hrs		
		Warranty	5 years		
•					
Product Dimensions		Suggested Accessory			
Weight (lbs.)	8.2	Microw	Microwave Sensor		
Height (in)	4.5	EM	EM driver		
Length (in)	13				
Width (in)	13				
Mounting Height (ft)					
Cable Length (ft)					
	Qual	ifications			
UL/ETL	Qual i UL	LM79	٧		
	·	1	V V		
Energy Star	·	LM79			
Energy Star DLC	UL	LM79 LM80	٧		
Energy Star DLC CEC	UL	LM79 LM80 IES File	٧		
UL/ETL Energy Star DLC CEC JA8 FCC	UL	LM79 LM80 IES File FDA	٧		