

|               | Prod                 | uct Spec |   |
|---------------|----------------------|----------|---|
| Category      | Troffer              |          | 4 |
| Item Code     | 9242                 |          |   |
| Stock Code    | LED-FXTF45/2X4/840G1 | PICTURE  |   |
| Mounting      | Ceiling              |          |   |
| Housing Color | White                |          |   |

| Electric Cha                                     | aracteristics | Photometric C           | haracteristics     |  |  |
|--|---------------|-------------------------|--------------------|--|--|
| Rated Wattage (W)                                | 45            | Lumen (lm)              | 5850               |  |  |
| Tested Wattage (W)                               | 45            | Efficacy (lm/w)         | 130                |  |  |
| nput Voltage (V)                                 | 120~277       | CRI                     | 80                 |  |  |
| /oltage Frequency (Hz)                           | 50/60         | сст (к)                 | 4000               |  |  |
| nput Current (A)                                 | 0.4           | Beam Angle (∘)          | 115                |  |  |
| Power Factor                                     | >0.9          | General Characteristics |                    |  |  |
| Replacement Wattage (W)                          | -             | Operating Temperature   | -4°F~104°F         |  |  |
| Surge protect level                              | 1KV           | Storage Temperature     | -4°F~140°F         |  |  |
| Dimmable   | 0-10V         | IP rating               | UL Damp Location   |  |  |
| ГНД  | <20%          | Rated Life              | 50000 hrs          |  |  |
|  |               | Warranty                | 5 years            |  |  |
|  |               |                         |                    |  |  |
|  |               |                         |                    |  |  |
| Product D  | imensions     | Suggested               | Suggested Accesory |  |  |
| Weight (lbs.)                                    | 13.3          | Motion                  | Motion Sensor      |  |  |
| Height (in)                                      | 3.55          | EM D                    | EM Driver          |  |  |
| Length (in)                                      | 47.72         |                         |                    |  |  |
| Width (in)                                       | 23.74         |                         |                    |  |  |
|  | 10            |                         |                    |  |  |
| Mounting Height (ft)                             |               |                         |                    |  |  |
| Mounting Height (ft)  Cable Length (ft)          |               |                         |                    |  |  |
|  |               |                         |                    |  |  |
|  |               |                         |                    |  |  |
|  |               | lifications             |                    |  |  |
| Cable Length (ft)                                | Qua<br>ETL    | lifications LM79        | ٧                  |  |  |
| Cable Length (ft)  UL/ETL                        |               |                         | ٧<br>٧             |  |  |
| Cable Length (ft)  UL/ETL Energy Star            |               | LM79                    |                    |  |  |
| Cable Length (ft)  UL/ETL Energy Star  DLC       |               | LM79<br>LM80            | ٧                  |  |  |
| Cable Length (ft)  UL/ETL  Energy Star  DLC  CEC |               | LM79 LM80 IES File      | ٧                  |  |  |
|  |               | LM79 LM80 IES File FDA  | ٧                  |  |  |