

	Produ	ct Spec	
Category	Linear High Bay		
Item Code	9287		
Stock Code	LED-FXHBL210/22FR/840	PICTURE	
Mounting	Chain Mount	1	
Housing Color	White		

Housing Color				
Electric Characteristics		Photometric Ch	Photometric Characteristics	
Rated Wattage (W)	210	Lumen (lm)	27463	
Tested Wattage (W)	210.21	Efficacy (lm/w)	131	
Input Voltage (V)	100~277	CRI	80	
Voltage Frequency (Hz)	50/60	сст (к)	4000	
Input Current (A)	1.8135	Beam Angle (∘)	100	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)	575-1000	Operating Temperature	-40°F~122°F	
Surge protect level	4KV	Storage Temperature	-40°F~122°F	
Dimmable	1-10V	IP rating	IP20	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
Product Dimensions		Suggested Accessory		
Weight (lbs.)		EM dri		
Weight (lbs.) Height (in)		EM dri Motion S	ver	
	22		ver ensor	
Height (in)	22	Motion S	ver ensor	
Height (in) Length (in)	22	Motion S	ver ensor	
Height (in) Length (in) Width (in)	22	Motion S	ver ensor	
Height (in)  Length (in)  Width (in)  Mounting Height (ft)		Motion S Yoke Mo	ver ensor	
Height (in)  Length (in)  Width (in)  Mounting Height (ft)		Motion S Yoke Motion S	ver ensor	
Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft)		Motion S Yoke Motion S LM79	ver ensor	
Height (in)  Length (in)  Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL  Energy Star	Qua	Motion S Yoke Motion S	ver ensor ount	
Height (in)  Length (in)  Width (in)  Mounting Height (ft)  Cable Length (ft)	Qua	Motion S Yoke Motion S LM79	ver ensor ount	
Height (in)  Length (in)  Width (in)  Mounting Height (ft)  Cable Length (ft)  UL/ETL  Energy Star  DLC	Qua	Motion S Yoke Motion S LM79 LM80	ver ensor ount	
Height (in)  Length (in)  Width (in)  Mounting Height (ft)  Cable Length (ft)  JL/ETL  Energy Star  DLC  CEC	Qua	Motion S Yoke Motion S  Hiffications  LM79 LM80 IES File	ver ensor ount	
Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft)	Qua	Motion S Yoke Motion S  Hilfications  LM79 LM80 IES File FDA	ver ensor ount	