

	Prod	uct Spec	
Category	LED Cut Off Wallpack		
Item Code	9319		
Stock Code	LED-FXCWP40/40K/BZ	PICTURE	
Mounting	Wall Mount		0
Housing Color	Bronze		

Housing Color	Bronze			
Electri	c Characteristics	Photometric	Characteristics	
Rated Wattage (W)	40	Lumen (lm)	5,288	
Tested Wattage (W)	40.41	Efficacy (lm/w)	120	
Input Voltage (V)	100~277	CRI	>70	
Voltage Frequency (Hz)	50/60	сст (к)	4000	
input Current (A)	0.34	Beam Angle (∘)	Forward Throw	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)	250	Operating Temperature	-40°F~122°F	
Surge protect level	4KV	Storage Temperature	-40°F~176°F	
Dimmable	1-10V	IP rating	IP65	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
			•	
		-		
Product Dimensions		Suggested Accessory		
Weight (lbs.)	6.83	Photocell		
Height (in)	9.25	EM driver		
Length (in)	14.17			
Width (in)	6.54			
wiuui (III)				
Mounting Height (ft)				
Mounting Height (ft)				
Mounting Height (ft)				
Mounting Height (ft)	Quali	fications		
Mounting Height (ft) Cable Length (ft)	Quali UL/cUL	fications LM79	V	
Mounting Height (ft) Cable Length (ft) UL/ETL	1		V V	
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	1	LM79		
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	UL/cUL	LM79 LM80	٧	
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	UL/cUL	LM79 LM80 IES File	٧	
Mounting Height (ft)	UL/cUL	LM79 LM80 IES File FDA	٧	