

	Produc	t Spec	
Category	Sport Lights		
Item Code	9324		
Stock Code	LED-FX16SPL650/33/850/BK/480	PICTURE	
Mounting	Yoke Mount	1	
Housing Color	Black		

Housing Color	Black			
Electric	Characteristics	Photometri	c Characteristics	
Rated Wattage (W)	650	Lumen (lm)	93869	
Tested Wattage (W)	652.91	Efficacy (lm/w)	144	
Input Voltage (V)	277~480	CRI	80	
Voltage Frequency (Hz)	50/60	ССТ (К)	5000	
nput Current (A)		Beam Angle (°)	NEMA 3x3	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)		Operating Temperature	-40°F~158°F	
Surge protect level	12KV	Storage Temperature	-40°F~158°F	
Dimmable	1-10V	IP rating	IP66	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	10 years	
Produ	ct Dimensions	Suggest	ed Accessory	
Weight (lbs.)	68		30ft long cable for remote mount	
Height (in)	20.75	20KV surge protector (Included w/ fixture)		
neight (m)	20.75	20KV surge protect	or (included w/ fixture)	
	14.13		or (included w/ fixture) Visor	
Length (in)				
Length (in) Width (in)	14.13			
Length (in)	14.13 17.48			
Length (in) Width (in) Mounting Height (ft)	14.13 17.48 25~50			
Length (in) Width (in) Mounting Height (ft)	14.13 17.48 25~50 10			
Length (in) Width (in) Mounting Height (ft) Cable Length (ft)	14.13 17.48 25~50 10			
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	14.13 17.48 25~50 10	ifications	Visor	
Length (in) Width (in) Mounting Height (ft)	14.13 17.48 25~50 10	ifications LM79	Visor	
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	14.13 17.48 25~50 10 Qual	ifications LM79 LM80	Visor	
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	14.13 17.48 25~50 10 Qual	ifications LM79 LM80 IES File	Visor	
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	14.13 17.48 25~50 10 Qual	ifications LM79 LM80 IES File FDA	Visor	