

Version	2.0	Date	9/28/2021
Prepared By	C.L.		

**PRODUCT SPECIFICATION**

Category	Flush Mount - Modern
Item Number	9356
Stock Code	LED12FMM-126L9CCT5-NI
Mounting	Surface
Housing Color	White + Sand Nickel



**ELECTRICAL CHARACTERISTICS**

Rated Wattage (W)	18	Replacement Wattage (W)	120
Tested Wattage (W)	18		
Input Voltage (V)	120	Surge Protect Level	DM=1KV, CM=2KV
Voltage Frequency (Hz)	60		
Input Current (A)	0.18	Dimmable	Incandescent Dimming
Power Factor	>0.9	AUX (12V) Line	No
THD	≤ 20%		

**PHOTOMETRIC CHARACTERISTICS**

Lumen (lm)	1260	CCT (K)	2700 / 3000 / 3500 / 4000 / 5000
Efficacy (lm/w)	70	Beam Angle (°)	110
CRI	90		

**GENERAL CHARACTERISTICS**


Operating Temperature (°F)	5 ~ 104
Storage Temperature (°F)	-4 ~ 113
IP Rating	Damp location
Rated Life	50000 hrs.
Warranty	5 years

**ACCESSORIES**

Item #	Stock Code	Description

**PRODUCT DIMENSIONS**

Width- in (mm)	12.13" (308mm)
Height- in (mm)	3.31" (84mm)
Depth- in (mm)	12.13" (308mm)
EPA (ft²)	N/A
Weight (lbs)	1.72
Mounting Height (ft)	>7.8
Cable Length (ft)	-



**CERTIFICATIONS**

UL/ETL	cETLus	CEC	✓
NSF/ETL Sanitation		JAB	✓
Energy Star	✓	FCC	✓
DLC		RoHs	✓

**DOCUMENTS**

LM79	✓	IES File	✓
LM80	✓	Dimmer List	✓

**COMMENTS**

--