

	Produc	t Spec	
Category	LED Bollard-Type 3		
Item Code	9387		
Stock Code	LED-FX8BLD18/42RT3/850/BZ	PICTURE	
Mounting	Floor (3 bolt anchor)		
Housing Color	Bronze		

Lumen (lm)  Efficacy (lm/w)  CRI  CCT (K)  Beam Angle (°)  General  Operating Temperature  Storage Temperature  IP rating  Rated Life  Warranty	ic Characteristics  1464 / 1098 / 73  81  >80  5000  Type 3  Characteristics  -22°F~122°F  -40°F~158°F  IP65  50000 hrs  5 years
CRI CCT (K) Beam Angle (*) General Operating Temperature Storage Temperature IP rating Rated Life Warranty	>80 5000 Type 3  Characteristics -22°F~122°F -40°F~158°F IP65 50000 hrs 5 years
CCT (K)  Beam Angle (*)  General  Operating Temperature  Storage Temperature  IP rating  Rated Life  Warranty	5000 Type 3  Characteristics  -22°F~122°F -40°F~158°F IP65 50000 hrs 5 years
Beam Angle (°)  General  Operating Temperature  Storage Temperature  IP rating  Rated Life  Warranty	Type 3  Characteristics  -22°F~122°F  -40°F~158°F  IP65  50000 hrs  5 years
General Operating Temperature Storage Temperature IP rating Rated Life Warranty	Characteristics  -22°F~122°F  -40°F~158°F  IP65  50000 hrs  5 years
Operating Temperature Storage Temperature IP rating Rated Life Warranty	-22°F~122°F -40°F~158°F IP65 50000 hrs 5 years
Storage Temperature IP rating Rated Life Warranty	-40°F~158°F IP65 50000 hrs 5 years
IP rating Rated Life Warranty	IP65 50000 hrs 5 years
Rated Life Warranty	50000 hrs 5 years
Warranty	5 years
Sugges	ted Accessory
Sugges	ted Accessory
•	
Qualifications	
LM79	٧
LM80	٧
IES File	٧
FDA	
NEMA	
Dimmer List	
2	LM79 LM80 IES File FDA NEMA