

	Produc	t Spec	
Category	Sport Lights		
Item Code	9396		
Stock Code	LED-FX16SPL400/44/840/BK/480	PICTURE	
Mounting	Yoke Mount	1	
Housing Color	Black		

Housing Color	Black			
Electric (Characteristics	Photometric (Characteristics	
Rated Wattage (W)	400	Lumen (lm)	55718	
Tested Wattage (W)	394.24	Efficacy (lm/w)	141	
Input Voltage (V)	277~480	CRI	80	
Voltage Frequency (Hz)	50/60	сст (к)	4000	
Input Current (A)		Beam Angle (°)	NEMA 4x4	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)		Operating Temperature	-40°F~158°F	
Surge protect level	10KV	Storage Temperature	-40°F~158°F	
Dimmable	1-10V	IP rating	IP66	
THD	<20%	Rated Life	50000 hrs	
		Warranty	10 years	
Produc	t Dimensions	Suggested	Accessory	
Weight (lbs.)	65		or remote mount	
Height (in)	20.75	20KV surge protector (Included w/ fixture)		
υ ()		Visor		
Length (in)	14.13	Vi	sor	
Length (in) Width (in)	14.13 17.48	Vi	sor	
Width (in)		Vi	sor	
	17.48	Vi	sor	
Width (in) Mounting Height (ft)	17.48 20~40	Vi	sor	
Width (in) Mounting Height (ft)	17.48 20~40 10	Vi	sor	
Width (in) Mounting Height (ft) Cable Length (ft)	17.48 20~40 10		v v	
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL	17.48 20~40 10 Qual	lifications		
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	17.48 20~40 10 Qual	lifications LM79	V	
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC	17.48 20~40 10 Qual	LM79 LM80	V V	
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	17.48 20~40 10 Qual	LM79 LM80 IES File	V V	
Width (in) Mounting Height (ft)	17.48 20~40 10 Qual	LM79 LM80 IES File FDA	V V	