## **NOTURALED**<sup>®</sup> Product Engineering Spec

	Prod	uct Spec	r		
Category	LED Slim Canopy				
Item Code	9416		E) a		
Stock Code	FX10SCM28/840/WH	PICTURE	A A		
Mounting	Ceiling				
Housing Color	White				
Floctr	ic Characteristics		Photomotr	ic Characteristics	
Rated Wattage (W)	28		Lumen (lm)	3512	
Tested Wattage (W)	28.19		Efficacy (lm/w)	125	
Input Voltage (V)	100~277		CRI	80	
Voltage Frequency (Hz)	50/60		CCT (K)	4000	
Input Current (A)	0.31		Beam Angle (°)	160	
Power Factor	>0.9			Characteristics	
Replacement Wattage (W)	>0.9	Oneratin	g Temperature	-40°F~122°F	
Surge protect level	4KV		ge Temperature	-40°F~140°F	
Dimmable	1-10	Storug	IP rating	IP65	
THD	<20%		Rated Life	50000 hrs	
	\$2070		Warranty	5 years	
			Warranty	5 years	
Product Dimensions			Suggested Accessory		
Weight (lbs.)	4.5			wave Sensor	
Height (in)	3.5		E	A driver	
Length (in)	9.48				
Width (in)	9.48				
Mounting Height (ft)					
Cable Length (ft)					
	-	· ·			
	Quali	fications			
UL/ETL	ETL/cETL		LM79	V	
Energy Star			LM80	V	
DLC	5.0 Premium		IES File	V	
CEC			FDA		
JA8			NEMA		
FCC	V		Dimmer List		
RoHS	V				
Comments:					