

Product Spec					
Category	LED Slim Canopy				
Item Code	9417	1	3		
Stock Code	FX10SCM28/850/WH	PICTURE			
Mounting	Ceiling				
Housing Color	White				

Housing Color	White			
Electric (Characteristics	Photometric Ch	aracteristics	
Rated Wattage (W)	28	Lumen (lm) 3746		
Tested Wattage (W)	28.19	Efficacy (lm/w)	125	
Input Voltage (V)	100~277	CRI	80	
Voltage Frequency (Hz)	50/60	сст (к)	5000	
Input Current (A)	0.31	Beam Angle (∘)	160	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)	150	Operating Temperature	-40°F~122°F	
Surge protect level	4KV	Storage Temperature	-40°F~140°F	
Dimmable	1-10	IP rating	IP65	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
Produc	t Dimensions	Suggested A	ccessorv	
Weight (lbs.)	4.5	Microwave		
Height (in)	3.5	EM dri		
Length (in)	9.48		•	
0 ()				
Width (in)	9.48			
Width (in) Mounting Height (ft)	9.48			
Width (in) Mounting Height (ft) Cable Length (ft)	9.48			
Mounting Height (ft)	9.48			
Mounting Height (ft)		lifications		
Mounting Height (ft) Cable Length (ft)		lifications LM79	V	
Mounting Height (ft) Cable Length (ft) UL/ETL	Qual		√ √	
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	Qual	LM79		
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC	Qual ETL/cETL	LM79 LM80	٧	
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	Qual ETL/cETL	LM79 LM80 IES File	٧	
Mounting Height (ft)	Qual ETL/cETL	LM79 LM80 IES File FDA	٧	