NOTURALED[®] Product Engineering Spec

	Prod	uct Spec		
Category	LED Slim Canopy			
Item Code	9418		, til	
Stock Code	FX10SCM42/840/BK	PICTURE		
Mounting	Ceiling			
Housing Color	Black			
_				
	ic Characteristics			ic Characteristics
Rated Wattage (W)	42		Lumen (lm)	5516
Tested Wattage (W)	41.42		Efficacy (lm/w)	133
Input Voltage (V)	100~277		CRI	80
Voltage Frequency (Hz)	50/60		CCT (K)	4000
Input Current (A)	0.42		Beam Angle (°)	160
Power Factor	>0.9		T	Characteristics
Replacement Wattage (W)	175	_	ng Temperature	-40°F~122°F
Surge protect level	4KV	Storag	ge Temperature	-40°F~140°F
Dimmable	1-10		IP rating	IP65
THD	<20%		Rated Life	50000 hrs
			Warranty	5 years
Prod	uct Dimensions		Suggested Accessory	
Weight (lbs.)	5.1		Microwave Sensor	
Haight (in)	3.5		E	M driver
Height (in)				
Length (in)	9.48			
	9.48			
Length (in)				
Length (in) Width (in)				
Length (in) Width (in) Mounting Height (ft)				
Length (in) Width (in) Mounting Height (ft)				
Length (in) Width (in) Mounting Height (ft)	9.48	fications		
Length (in) Width (in) Mounting Height (ft) Cable Length (ft)	9.48	fications	LM79	√
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL	9.48 Quali	fications	LM79 LM80	√ √ √
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	9.48 Quali	fications		
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC	9.48 Quali	fications	LM80	٧
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	9.48 Quali	fications	LM80 IES File	٧
Length (in) Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC JA8	9.48 Quali	fications	LM80 IES File FDA	٧
Length (in) Width (in) Mounting Height (ft)	9.48 9.48 Quali 5.0 Premium	fications	LM80 IES File FDA NEMA	٧