

Product Spec				
Category	LED Slim Canopy		of the same	
Item Code	9424		8	
Stock Code	FX10SCM59/840/WH	PICTURE		
Mounting	Ceiling			
Housing Color	White			

Housing Color	White			
Electri	c Characteristics	Photometric	Characteristics	
Rated Wattage (W)	59	Lumen (lm)	7694	
Tested Wattage (W)	57.4	Efficacy (lm/w)	134	
Input Voltage (V)	100~277	CRI	80	
Voltage Frequency (Hz)	50/60	сст (к)	4000	
Input Current (A)	0.6	Beam Angle (∘)	160	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)	250	Operating Temperature	-40°F~122°F	
Surge protect level	4KV	Storage Temperature	-40°F~140°F	
Dimmable	1-10	IP rating	IP65	
THD	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
			-	
Produ	uct Dimensions	Suggeste	Suggested Accessory	
Weight (lbs.)	5.1	Microw	Microwave Sensor	
Height (in)	3.5	EM	EM driver	
Length (in)	9.48			
	0.40			
Width (in)	9.48			
Width (in) Mounting Height (ft)	9.48			
Mounting Height (ft)	9.48			
	9.48			
Mounting Height (ft)	9.48			
Mounting Height (ft)		lifications		
Mounting Height (ft) Cable Length (ft)		lifications LM79	٧	
Mounting Height (ft) Cable Length (ft) UL/ETL	Qua		V V	
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	Qua	LM79		
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	Qua ETL/cETL	LM79 LM80	٧	
Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC CEC	Qua ETL/cETL	LM79 LM80 IES File	٧	
Mounting Height (ft)	Qua ETL/cETL	LM79 LM80 IES File FDA	٧	