

| | Produ | ict spec | - | | |
|---|---|----------------|---|--------------------|--|
| Category | LED Cut Off Wallpack | | | | |
| ltem Code | 9443 | | | | |
| Stock Code | LED-FXCWP80/40K/BZ | PICTURE | | + | |
| Mounting | Wall Mount |] 💋 | | | |
| Housing Color | Bronze | | V | | |
| | | | | | |
| | c Characteristics | | | ic Characteristics | |
| Rated Wattage (W) | 80 | - | Lumen (lm) | 11,048 | |
| Sested Wattage (W) | 80.71 | | Efficacy (lm/w) | 123 | |
| nput Voltage (V) | 100~277 | CRI | | >70 | |
| oltage Frequency (Hz) | 50/60 | CCT (K) | | 4000 | |
| nput Current (A) | 0.6725 (@120Vac) | Beam Angle (°) | | Forward Throw | |
| Power Factor | >0.9 | | General Characteristics | | |
| eplacement Wattage (W) | 400~575 | | g Temperature | -40°F~122°F | |
| urge protect level | 4KV | Storag | e Temperature | -40°F~176°F | |
| Dimmable | 1-10V | | IP rating | IP65 | |
| THD | <20% | | Rated Life | 50000 hrs | |
| | | | Warranty | 5 years | |
| | | | | | |
| | • | - | | | |
| Product Dimensions | | | Suggested Accessory | | |
| | = 10 | | Photocell | | |
| Weight (lbs.) | 7.48 | | | | |
| Weight (lbs.) Height (in) | 9.25 | | E | M driver | |
| | | | E | M driver | |
| Height (in) | 9.25 | | E | M driver | |
| Height (in) Length (in) | 9.25 14.17 | | E | M driver | |
| Height (in) Length (in) Width (in) Mounting Height (ft) | 9.25 14.17 | | E | M driver | |
| Height (in) Length (in) Width (in) | 9.25 14.17 | | E | M driver | |
| Height (in) Length (in) Width (in) Mounting Height (ft) | 9.25 14.17 | | E | M driver | |
| Height (in) Length (in) Width (in) Mounting Height (ft) | 9.25 14.17 6.54 | ications | E | M driver | |
| Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) | 9.25 14.17 6.54 | ications | E | M driver | |
| Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) JL/ETL | 9.25 14.17 6.54 Qualif | ications | LM79 | | |
| Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) Cable Length (ft) | 9.25 14.17 6.54 Qualif | ications | LM79 LM80 | V V V | |
| Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) L/ETL Chergy Star | 9.25 14.17 6.54 Qualif | ications | LM79 LM80 IES File | √ | |
| Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) Cable Length (ft) UL/ETL Energy Star DLC EEC | 9.25 14.17 6.54 Qualif | ications | LM79 LM80 IES File FDA | V V V | |
| Height (in) Length (in) Width (in) Mounting Height (ft) Cable Length (ft) L/ETL Energy Star DLC EEC | 9.25 14.17 6.54 Qualif UL/cUL V5.1 Premiun | ications | LM79 LM80 IES File FDA NEMA | V V V | |
| Height (in) Length (in) Width (in) Mounting Height (ft) | 9.25 14.17 6.54 Qualif | ications | LM79 LM80 IES File FDA | V V V | |