

	Prod	uct Spec	
Category	LED Cut Off Wallpack		
Item Code	9446		
Stock Code	LED-FXCWP120/50K/BZ	PICTURE	
Mounting	Wall Mount		
Housing Color	Bronze		

Housing Color	Bronze			
Electric	Characteristics	Photometric	Characteristics	
Rated Wattage (W)	120	Lumen (lm)	16,776	
Tested Wattage (W)	121	Efficacy (lm/w)	120	
nput Voltage (V)	100~277	CRI	>70	
Voltage Frequency (Hz)	50/60	CCT (K)	5000	
nput Current (A)	1.002 (@120Vac)	Beam Angle (∘)	Forward Throw	
Power Factor	>0.9	General Characteristics		
Replacement Wattage (W)	400~750	Operating Temperature	-40°F~122°F	
Surge protect level	6KV	Storage Temperature -40°F~176°F		
Dimmable	1-10V	IP rating	IP65	
ГНД	<20%	Rated Life	50000 hrs	
		Warranty	5 years	
Produ	act Dimensions	Suggeste	ed Accessory	
Weight (lbs.)	10.56		Suggested Accessory Photocell	
Height (in)	9.25		EM driver	
mergine (m)	7.20	21.	411701	
Length (in)	14.17			
Length (in) Width (in)	14.17 9.65			
Width (in)	14.17 9.65			
Width (in) Mounting Height (ft)				
Width (in) Mounting Height (ft)	9.65	fications		
Width (in) Mounting Height (ft) Cable Length (ft)	9.65	fications LM79	٧	
Width (in) Mounting Height (ft) Cable Length (ft)	9.65 Quali		V V	
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star	9.65 Quali	LM79		
Width (in) Mounting Height (ft) Cable Length (ft) JL/ETL Energy Star	9.65 Quality	LM79 LM80	٧	
Width (in) Mounting Height (ft) Cable Length (ft) UL/ETL Energy Star DLC	9.65 Quality	LM79 LM80 IES File	٧	
Width (in) Mounting Height (ft)	9.65 Quality	LM79 LM80 IES File FDA	٧	