


natural^{led}®

Product Engineering Spec

Product Spec			
Category	LED Wall Pack	PICTURE	
Item Code	9454		
Stock Code	FXTWP28/50K/BZ-PHO		
Mounting	Wall Mount		
Housing Color	Bronze		

Electric Characteristics		Photometric Characteristics	
Rated Wattage (W)	28	Lumen (lm)	4189
Tested Wattage (W)	28.22	Efficacy (lm/w)	148
Input Voltage (V)	120~277	CRI	80
Voltage Frequency (Hz)	50/60	CCT (K)	5000
Input Current (A)	0.24 (@120V)	Beam Angle (°)	Forward Throw
Power Factor	>0.9	General Characteristics	
Replacement Wattage (W)	175~250	Operating Temperature	-22°F~122°F
Surge protect level	4KV	Storage Temperature	-40°F~140°F
Dimmable	0-10V	IP rating	IP65
THD	<20%	Rated Life	50000 hrs
		Warranty	5 years

Product Dimensions		Suggested Accessory	
Weight (lbs.)	5.51	120~277V AC EM driver - Item# 7336	
Height (in)	9.21	Microwave Sensor - Item# P10234	
Depth	7.29		
Width (in)	9.05		
Mounting Height (ft)			
Cable Length (ft)			

Qualifications			
UL/ETL	ETL/cETL	LM79	√
Energy Star		LM80	√
DLC	V5.1 Premium	IES File	√
CEC		FDA	
JA8		NEMA	
FCC	√	Dimmer List	
RoHS	√		

Comments:

Photocell Included with Fixture