

|             |      |      |         |
|-------------|------|------|---------|
| Version     | 2.0  | Date | 7/22/21 |
| Prepared By | C.L. |      |         |

| PRODUCT SPECIFICATION |                      |
|-----------------------|----------------------|
| Category              | Troffer              |
| Item Number           | 9559                 |
| Stock Code            | FXTF36SW/2X2/8CCT3G1 |
| Mounting              | Ceiling              |
| Housing Color         | White                |



| ELECTRICAL CHARACTERISTICS |              |                         |          |
|----------------------------|--------------|-------------------------|----------|
| Rated Wattage (W)          | 36 / 30 / 20 | Replacement Wattage (W) | 60 ~ 100 |
| Tested Wattage (W)         | 36           |                         |          |
| Input Voltage (V)          | 120 ~ 277    | Surge Protect Level     | 2KV      |
| Voltage Frequency (Hz)     | 50/60        | Dimmable                | 0-10V    |
| Input Current (A)          | max 0.34     | AUX (12V) Line          | No       |
| Power Factor               | >0.9         |                         |          |
| THD                        | ≤ 20%        |                         |          |

| PHOTOMETRIC CHARACTERISTICS |                 |                |      |
|-----------------------------|-----------------|----------------|------|
| Lumen (lm)                  | 4572/3900/2640  | CCT (K)        | 3500 |
| Lumen (lm)                  | 4896 /4140/2800 | CCT (K)        | 4000 |
| Lumen (lm)                  | 4680/ 3960/2680 | CCT (K)        | 5000 |
| Efficacy (lm/w)             | >127            | Beam Angle (°) | 115  |
| CRI                         | 80              |                |      |

| GENERAL CHARACTERISTICS    |                  |
|----------------------------|------------------|
| Operating Temperature (°F) | -4 ~ 104         |
| Storage Temperature (°F)   | -4 ~ 140         |
| IP Rating                  | UL Damp Location |
| Rated Life                 | 50000 hrs.       |
| Warranty                   | 5 Years          |

| ACCESSORIES |                |                                      |
|-------------|----------------|--------------------------------------|
| Item #      | Stock Code     | Description                          |
| K7334225    | FXTF-BAEM-MT   | Emergency Driver Kit (7334 + P10225) |
| P10438      | SEN-HB001VCR-1 | 12V Motion Sensor 0-10V              |
| P10228      | MT-2X2FMBOX    | Flange Mount Kit                     |
| P10147      | MT-ACC-4FT     | Air Craft Cable - 4ft                |

\*See Page 2 for more accessories

| PRODUCT DIMENSIONS   |                 |  |
|----------------------|-----------------|--|
| Width- in (mm)       | 23.74" (603 mm) |  |
| Height- in (mm)      | 1.97" (50 mm)   |  |
| Depth- in (mm)       | 23.74" (603 mm) |  |
| EPA (ft²)            | N/A             |  |
| Weight (lbs)         | 8               |  |
| Mounting Height (ft) | 10              |  |
| Cable Length (ft)    | -               |  |

| CERTIFICATIONS       |               |      |   |
|----------------------|---------------|------|---|
| UL/ETL               | ETL/ cETL     | CEC  |   |
| NSF / ETL Sanitation |               | JA8  |   |
| Energy Star          |               | FCC  | ✓ |
| DLC                  | V5.1 Standard | RoHs | ✓ |

| DOCUMENTS |   |             |   |
|-----------|---|-------------|---|
| LM79      | ✓ | IES File    | ✓ |
| LM80      | ✓ | Dimmer List |   |
|           |   |             |   |
|           |   |             |   |

