


Version	2.0	Date	5/18/2021
Prepared By	C.L.		

PRODUCT SPECIFICATION	
Category	Vapor Tight
Item Number	9564
Stock Code	FXVTL100SW/96FR/850
Mounting	Ceiling , Wall Mount
Housing Color	Grey + Frosted PC lens



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	100 / 80 / 60	Replacement Wattage (W)	2 x 110W T12
Tested Wattage (W)	100		
Input Voltage (V)	120 ~ 277	Surge Protect Level	4KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.91 (@120)	AUX (12V) Line	No
Power Factor	>0.9		
THD	≤ 20%		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	13586 / 10400 8108	CCT (K)	5000
Efficacy (lm/w)	130	Beam Angle (°)	110
CRI	> 80		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	-40 ~ 122
Storage Temperature (°F)	-40 ~ 158
IP Rating	IP66
Rated Life	50000 hrs.
Warranty	5 years
NEMA rated enclosure	NEMA - 4X

ACCESSORIES		
Item #	Stock Code	Description
P10234	SEN-MC605V-D	120V ~ 277V Microwave Motion Sensor
K7334412	FXVTL-BAEM-MTG1	120V ~ 277V 15W EM Driver Kit
P10389	SPD-L-10KV-277	10KV Surge protector - 120V ~ 277V
P10390	SPD-L-20KV-277	20KV Surge protector - 120V ~ 277V

PRODUCT DIMENSIONS		
Width- in (mm)	5.04" (128mm)	
Height- in (mm)	4" (103mm)	
Depth- in (mm)	94.5" (2400mm)	
EPA (ft²)	N/A	
Weight (lbs)	11.68 Lbs.	
Mounting Height (ft)	10 ~ 20	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	ETL/cETL	CEC	
NSF/ETL Sanitation	✓	JA8	
Energy Star		FCC	✓
DLC	V5.1 Standard	RoHS	✓

DOCUMENTS			
LM79	✓	IES File	✓
LM80	✓	Dimmer List	

COMMENTS