

Version	2.0	Date	9/27/2021
Prepared By	C.L.		

**PRODUCT SPECIFICATION**

Category	Industrial Round Highbay
Item Number	9573
Stock Code	FX16HBR200/110/850/IP66/480
Mounting	Pole Mount / Yoke Mount
Housing Color	Black



**ELECTRICAL CHARACTERISTICS**

Rated Wattage (W)	200	Replacement Wattage (W)	1000 ~ 1500
Tested Wattage (W)	200		
Input Voltage (V)	277 ~ 480	Surge Protect Level	10KV
Voltage Frequency (Hz)	50/60	Dimmable	0-10V
Input Current (A)	0.76 (@277V)	AUX (12V) Line	YES
Power Factor	>0.9		
THD	≤ 20%		

**PHOTOMETRIC CHARACTERISTICS**

Lumen (lm)	36281	CCT (K)	5000
Efficacy (lm/w)	181	Beam Angle (°)	110
CRI	80		

**GENERAL CHARACTERISTICS**



Operating Temperature (°F)	-40 ~ 158
Storage Temperature (°F)	-40 ~ 140
IP Rating	IP66
Rated Life	50000 hrs.
Warranty	5 Years

**ACCESSORIES**

Item #	Stock Code	Description
P10390	SPD-L-20KV-277	Surge protector - Long, 20KV 120-277V
P10391	SPD-L-20KV-480	Surge protector - Long, 20KV 347-480V
P10233	MT-PIPE075-MPT-18in/BK	3/4" 18in Black Steel Pipe-Male (NPT)
P10439	MT-YK-HBR16-BK	Yoke mount-16" Industrial High Bay Round Black
P10440	CVR-16HBR-80-AL	80deg AL(aluminum) reflector
	Wireless controller	*Please contact us for model#

**PRODUCT DIMENSIONS**

Width- in (mm)	15.75" (400mm)
Height- in (mm)	11.02" (280mm)
Depth- in (mm)	15.75" (400mm)
EPA (ft²)	N/A
Weight (lbs)	20.95
Mounting Height (ft)	25 ~ 50
Cable Length (ft)	7.5



**CERTIFICATIONS**

UL/ETL	cETLus	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC	V5.1 Standard	RoHs	✓

**DOCUMENTS**

LM79	✓	IES File	✓
LM80	✓	Dimmer List	

**COMMENTS**

--	--	--	--