naturaled®

Version	2.0	Date	8/11/2022
Prepared By	J.C		

	PRODUCT SPECIFICATION						
Category		LED Slim Wallpack			PICTURE		
Item Number		9589					
Stock Code	FXSW	/P45SW/8CCT3/BZ/34	7-PHO				
Mounting		Wall mount					
Housing Color		Bronze					
	ELECTRICAL CH	ARACTERISTICS		TI		PHOTOMETRIC CH	
Datad Mattaga (M)	45/20/15			1 1			

ELECTRICAL CHARACTERISTICS						
Rated Wattage (W)	45/28/15					
Tested Wattage (W)		Replacement Wattage (W)	-			
Input Voltage (V)	120-347					
Voltage Frequency (Hz)	50/60	Surge Protect Level	4KV			
Input Current (A)	0.41	Dimmable	0-10V			
Power Factor	≥ 0.9	AUX (12V) Line	-			
THD	<20%					

PHOTOMETRIC CHARACTERISTICS						
Lumen (lm)	5400/3360/1800	ССТ (К)	30/40/50K			
Efficacy (lm/w)	120lm/w	Beam Angle (°)	Flood			
CRI	> 80					
	•	•				

	GENERAL CHARACTERISTICS				
Operating Temperature (°F)	-22 ~ 122				
Storage Temperature (°F)	-40 ~ 158				
IP Rating	IP65				
Rated Life	50000 hrs.				
Warranty	5 years				

ACCESSORIES				
ltem #	Stock Code	Description		

6

Ī

10 II

			PRODUCT DIMENSIONS
Width- in (mm)	6.57"	167mm	6.57″
Height- in (mm)	7.87"	200mm	167mm
Depth- in (mm)	3.94"	100mm	
EPA (ft²)		-	2.36"
Weight (lbs)		4.4	
Mounting Height (ft)		-	
Cable Length (ft)		-	1

CERTIFICATIONS				DOCUMENTS			
UL/ETL	ETL/cETL	CEC		LM79	1	IES File	1
NSF/ETL Sanitation		8AL		LM80	1	Dimmer List	-
Energy Star		FCC	1				
DLC	5.1 Premium	RoHs	1				

COMMENTS	