



**Contractor Essentials**  
LIGHT MORE, PAY LESS  
BY LIGHT BULB SURPLUS

# WALL PACK - WP08

## DESCRIPTION

Combined with high-efficiency light engine, the classic WP08 LED wall pack family features a high-quality UV-resistant PC lens, which provides excellent lighting. It combines low cost, high performance with controls and emergency options.



## SPECIFICATION FEATURES

### Construction

- Sealed die-casting profile for outdoor applications.
- Casting thermally conducts LED heat to optimize performance and long life.
- Suitable for applications requiring 3G testing prescribed by ANSI C136.31.

### Optics

- Single CCT 4000K and 5000K are available for standard version, and the 65W, 100W offer the color tunable version, the CCT can be changed to 3000K/4000K/5000K.
- Scalable Lumen Packages from 3,400 to 15,000 Lumens.
- UV stabilized polycarbonate is available for the optic lens, the professional prismatic design offers a good light distribution control and guarantees the uniformity.

### Electrical

- Universal 120-277 VAC input voltage.
  - 1-10V Dimming.
  - Both drivers have a power factor >90%, THD <20%.
  - Operating Temperature Range: -40°C to 40°C (-40°F - + 104°F).
- Note: Operating with emergency battery temperature range: 10°C to 40°C (+50°F - + 104°F).

### Lifespan

- Estimated 50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

### Warranty

- Five-year warranty.

### Certifications

- UL cUL wet location listed.
  - DesignLights Consortium™ Qualified.
- Note: DesignLights Consortium™ Qualified and classified for DLC Standard (all lumen packages), refer to [www.designlights.org](http://www.designlights.org) for details.



### Note

- Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 C (±5 C ) specifications subject to change without notice.



## DIMENSIONS

unit: mm/inch




Net Weight  
30W: 6.327lb  
40W: 6.525lb  
65W: 6.724lb  
90W&100W: 7.319lb  
125W: 8.157lb

## PERFORMANCE DATA

SYSTEM WATTS	VOLTAGE	CRI	LUMENS (4000K)	LPW (4000K)	LUMENS (5000K)	LPW (5000K)
30W	120-277VAC	70	3400lm	113 lm/W	3500lm	117 lm/W
40W	120-277VAC	70	5000lm	125 lm/W	5100lm	128 lm/W
65W	120-277VAC	70	7800lm	120 lm/W	7900lm	122 lm/W
90W	120-277VAC	70	10500lm	117 lm/W	10500lm	117 lm/W
125W	120-277VAC	70	15000lm	120 lm/W	15000lm	120 lm/W

## PHOTOMETRICS



## ACCESSORIES



### Photocell

USE: Photocell is field installed or pre-installed in factory by requesting



### Emergency Battery Backup

USE: It can be pre-installed in factory or field installed  
Only suitable for 30W,40W,65W,90W,100W.



### Power and CCT controller

USE: The wattage and CCT can be changed by switch selection on the controller.  
Only suitable for 65W & 100W.

## ORDERING GUIDE

Example: WP08 40W 27V 50K Y Y Y Y Y

Fixture Type	Wattage	Voltage	CCT	Finish	Photocell (Option)	Emergency Battery (Option)	CCT and Power Adjustable	Internal Code
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<b>WP08</b> Wall Pack Series	<b>30</b> 30W <b>40</b> 40W <b>65</b> 65W <b>90</b> 90W <b>100</b> 100W <b>125</b> 125W	<b>27V</b> 120-277V	<b>40K</b> 4000K <b>50K</b> 5000K	<b>D</b> Dark Bronze <b>B</b> Black <b>W</b> White	<b>P0</b> 120-277V Photocell <b>Blank</b> Without Photocell	<b>B<sup>2</sup></b> Emergency Battery <b>Blank</b> Without Emergency Battery	<b>AD<sup>1</sup></b> With Adjustment Dial <b>Blank</b> Without Adjustment Dial	<b>Blank</b> <b>Alphanumeric</b>

Note: 1. Only the 65W & 100W optional for DDK and AD.  
2. Only 125W not suitable for emergency battery.