

Specifications

Input Voltage	Dimmable models: 120V only (TRIAC Dimmer) Non-dimmable models: 110-277V
Base	G5
CRI	>80
LED Type	LM80 2835
Lens Type	Frosted
Power Factor	>0.9
Color Temp.	3500K, 4000K, 5000K
Beam Angle	140°
Light Efficacy	120 LM/W
Operating Temp.	-4°F ~ +104°F
Warranty	5-year

Description

Aleddra's new T5 LED Integrated (T5N) Lamps are designed to perform efficiently in conditions where fluorescent, halogen and low voltage luminaires have traditionally been used. Our lamps incorporate integral drivers, are self-supporting, and can be surface-mounted. Individual units can be chained together, making a desirable illumination space. Instant start within one second once power on. T5N Lamps connect directly to line voltage and can be used in any interior space. Ideal for under-cabinets in kitchens, offices, schools, hospitals, grocery stores and more.

Available accessories to order separately:



Magnetic Holder

INT-M2M

INT-PC

INT-PC-SWITCH

Features

- Operates directly from line voltage
- Usable as a stand alone fixture
- Individual units can be plugged together for continuous lengths up to 30ft
- Suitable for damp locations
- Good heat dissipation
- Rated lifetime of 50,000 hrs
- DLC Listed for utility rebate
- Dimmable models support only 120V TRIAC dimmer
- Installation Kit included:



T5-EC



12" T5 Power Connector



Clip



Plastic Anchor 2pcs




Self-tapping Screw 2 pcs

Product Compliance & Certifications:

- ETL
- DLC

Dimensions



Ordering Information

Product Model #	Wattage	Color	Lumen	Length	Dimmable
LLT-T5N-2-35K	9W	3500K	1035lm	2ft	No
LLT-T5N-2-40K	9W	4000K	1035lm	2ft	No
LLT-T5N-2-50K	9W	5000K	1035lm	2ft	No
LLT-T5N-3-35K	12W	3500K	1380lm	3ft	No
LLT-T5N-3-40K	12W	4000K	1380lm	3ft	No
LLT-T5N-3-50K	12W	5000K	1380lm	3ft	No
LLT-T5N-4-35K	16W	3500K	1840lm	4ft	No
LLT-T5N-4-40K	16W	4000K	1840lm	4ft	No
LLT-T5N-4-50K	16W	5000K	1840lm	4ft	No
LLT-T5N-1-D-35K	5W	3500K	575lm	1ft	Yes
LLT-T5N-1-D-40K	5W	4000K	575lm	1ft	Yes
LLT-T5N-1-D-50K	5W	5000K	575lm	1ft	Yes
LLT-T5N-2-D-35K	9W	3500K	1035lm	2ft	Yes
LLT-T5N-2-D-40K	9W	4000K	1035lm	2ft	Yes
LLT-T5N-2-D-50K	9W	5000K	1035lm	2ft	Yes
LLT-T5N-3-D-35K	12W	3500K	1380lm	3ft	Yes
LLT-T5N-3-D-40K	12W	4000K	1380lm	3ft	Yes
LLT-T5N-3-D-50K	12W	5000K	1380lm	3ft	Yes
LLT-T5N-4-D-35K	16W	3500K	1840lm	4ft	Yes
LLT-T5N-4-D-40K	16W	4000K	1840lm	4ft	Yes
LLT-T5N-4-D-50K	16W	5000K	1840lm	4ft	Yes

* This lamp cannot be used with emergency ballast.