











Energy Efficient











LED DOWNLIGHT

Model No. DLC-5020e

 $\ \, \mathsf{LED} \,\, \textit{\textbf{DLC-5020e}}, \, \mathsf{Durable} \,\, \mathsf{and} \,\, \mathsf{dependable}, \, \mathsf{this} \,\, \mathsf{LED} \,\, \mathsf{downlight} \,\, \mathsf{seamlessly} \,\, \mathsf{spreads} \,\, \mathsf{even} \,\,$ Warm White (2700K) color, reduces maintenance expenses, and guarantees true color perception. The Euri Lighting **DLC-5020e** replaces the standard 120-Watt incandescent bulb by only using 18-Watts to output an exceptional 1260 lumens. A cut above the rest, this LED downlight allows for easy retrofit installation in 5-6" recessed light housings.











Electrical Specifications

Model No.	Input Power	Input Voltage	Lumen Output	Beam Angle	Center Beam	CCT
DLC-5020e	18 W	120 V	1260 lm	96°	N/A	2700 K

CRI	Luminous Efficacy	Power Factor	Input Current	Base	Lamp Lifespan	Estimated Yearly Cost
90+	70 lm/W	0.9	0.16 A	E26 Adapter	35,000 Hrs.	\$2.16

Mechanical Specifications

Rating	Operational Temperature	Inner Box QTY.	Master Box QTY.	Dimensions(in.)	UPC Code
Damp Rated	-4°F - 104°F	N/A	12 pcs	5.43"(ø) x 2.75"(H)	811174030898

Product Dimensions

Product Photometric Data



