

Single End 0-10V dimming Lamps

Internal Driver LED Lamp Single End Input



Flex™
Internal Driver LED Lamp

Features & Benefits

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes non-shunted(rapid start) sockets
- Compatible 0-10V Dimming System
- Works in cold temperature applications
- Suitable for damp and dry locations
- -20° F to 130° F ambient operating temperature
- Glass tube for superior optical performance
- 5 Year Warranty
- Superior Wide View Angle

Product Certification



* EMERGENCY BALLAST RESTRICTIONS

Specification


Model No.	Length	Base type	Lamp Wattage	Input Voltage	CCT	Initial Lumens	CRI	Beam Angle	LPW	Power Factor	THD
L36T8/830/12G-ID-10V	36	G13	12	120-277	3000	1400	83	325	115	0.9	<20%
L36T8/835/12G-ID-10V	36	G13	12	120-277	3500	1400	83	325	115	0.9	<20%
L36T8/840/12G-ID-10V	36	G13	12	120-277	4000	1400	83	325	115	0.9	<20%
L36T8/850/12G-ID-10V	36	G13	12	120-277	5000	1400	83	325	115	0.9	<20%

Order Information


EXAMPLE: L48T8/840/14G-ID-10V												
L	48	T8	8	40	14 G	-	ID	-	10V			
Manufacturer's Code	Normal Lamp Length 48=48"	Lamp Shape T8=T8	CRI 8=>80	CCT		Wattage 14G-14W	Internal Driver				0-10V dimming	
				50=5000K	40=4000K							
				35=3500K								

Wiring Diagram

Note: Will not operate on shunted sockets. Use only with non-shunted(rapid start) sockets.



Non-Shunted(rapid Start Socket)



Shunted(Instant Start Socket)

Dlc Information

Model No.	DLC Product ID	DLC Product Model	DLC Version
L36T8/830/12G-ID-10V	N/A	N/A	N/A
L36T8/835/12G-ID-10V	N/A	N/A	N/A
L36T8/840/12G-ID-10V	N/A	N/A	N/A
L36T8/850/12G-ID-10V	N/A	N/A	N/A