

#### Features

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

Advanced dimming with Pro-DIM technology: 0-10V and/or AB dimming  
No Polarity: lamp ends can be reversed  
Same wiring as fluorescent lamp/ballast system  
UL 1598C for safety  
  
No Mercury, No UV  
Suitable for Dry and Damp Locations  
Low Temperature Operation  
Instant On  
50,000 hours with no limitation on On/Off Cycles  
5-year Warranty  
Evaluated for use in totally enclosed, recessed luminaires, surface mount wall and ceiling luminaires, outdoor luminaires (open surface mount luminaires with compartment protection from weather)  
For use with Class 2 driver only

### CoreTech LED Series

#### PRODUCT SPECIFICATIONS

Model	Lamp Input Current	System Wattage	Lamp Wattage	Length	CRI	Initial Lumens	Lamp Efficacy (lm/W)	System Efficacy (lm/W)	Beam Angle	CCT	DLC
-------	--------------------	----------------	--------------	--------	-----	----------------	----------------------	------------------------	------------	-----	-----

#### Wiring diagram





Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.

Espen Technology, Inc. | 12257 Florence Avenue | Santa Fe Springs, CA 90670 | Phone: (562) 529-2938 | Fax: (562) 529-2978  
Toll Free: (866) 933-7736 | Email: [info@espentech.com](mailto:info@espentech.com) | [www.espentech.com](http://www.espentech.com)