



CLD18WV/8XX-MB	
Std. Pack Qty.	50
Order Code	CLD18WV/827-MB
	CLD18WV/835-MB
	CLD18WV/850-MB
	CLD18WV/830-MB
	CLD18WV/840-MB

PRODUCT SPECIFICATION

COMPACT LED RETROFIT BULB

GENERAL CHARACTERISTICS

Lamp Type	Compact LED Retrofit Ballast Compatible Bulb
Voltage	120-277V, or 347V (Depend on Ballast Spec)
Base	G24d
Lamp Wattage	9
System Wattage	12
Rated Avg. Life (hrs)	50,000
Replacement	18W, 26W, 32W, 42W CFQ

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	900
Beam Angle	120
Color Temperature	2700K
	3500K
	5000K
	3000K
	4000K
Color Rendering Index (CRI)	82

DIMENSIONS


Overall Length (inches) (D)	4.68
Base Face to Top of Lamp (inches) (C)	4.05
Front (inches) (A)	1.85
Side (inches) (B)	1.85

FEATURES

- Comply with UL 1993, UL8750
- Comply with FCC 47 Part 15 Class B
- 18W/26W G24d magnetic ballast compatible
- No UV, No Mercury
- Quick Installation
- High Lumen
- Extended Life
- High Quality Color Rendering
- Five Year Limited Warranty



Dimension Layout



DLC Information

Order Code	DLC Product ID	DLC Product Model	DLC Version
CLD18WV/827-MB	N/A	N/A	N/A
CLD18WV/830-MB	N/A	N/A	N/A
CLD18WV/835-MB	N/A	N/A	N/A
CLD18WV/840-MB	N/A	N/A	N/A
CLD18WV/850-MB	N/A	N/A	N/A

* Please refer to "[Ballast Compatibility List](#)" on Related Downloads.

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.