

### Features

- 0-10V dimming (10-100%)
  - No Polarity: lamp ends can be reversed
  - Same wiring as fluorescent lamp/ballast system
  - UL 1598C for safety
  - Full glass as fluorescent T8
  - No Mercury, No UV
  - Suitable for Dry and Damp Locations
  - Low Temperature Operation
  - Instant On
  - 50,000 hours with no limitation on On/Off Cycles
  - 5-year Warranty
- Evaluated for use in totally enclosed, recessed luminaires, surface mount wall and ceiling luminaires, outdoor luminaires (open surface mount luminaires with compartment protection from weather)
- For use with Class 2 driver only



LED Lamp

## CoreTech LED Series

### Specification Data

Model	Lamp Input Current	System Wattage	Lamp Wattage	Length	CRI	Initial Lumens	Lamp Efficacy (lm/W)	System Efficacy (lm/W)	Beam Angle	CCT
L48T8/940/15G-XT	250mA	13	10	48"	90	1660	166	128	325	4000K
L48T8/940/15G-XT	300mA	15	12	48"	90	1920	160	128	325	4000K
L48T8/940/15G-XT	360mA	17	15	48"	90	2350	168	139	325	4000K

### Wiring Diagram



### DLC Information

Order Code	Lamp Input Current	DLC Product ID	DLC Product Model	DLC Product Version
L48T8/940/15G-XT	250mA	N/A	N/A	N/A
L48T8/940/15G-XT	300mA	N/A	N/A	N/A
L48T8/940/15G-XT	360mA	PRREYCSZ	L48T8/940/15G-XT	5.1

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.