

Features

- 0-10V dimming (10-100%)
 - No Polarity: lamp ends can be reversed
 - Same wiring as fluorescent lamp/ballast system
 - UL 1598C for safety
 - Full glass as fluorescent T8
 - No Mercury, No UV
 - Suitable for Dry and Damp Locations
 - Low Temperature Operation
 - Instant On
 - 50,000 hours with no limitation on On/Off Cycles
 - 5-year Warranty
- Evaluated for use in totally enclosed, recessed luminaires, surface mount wall and ceiling luminaires, outdoor luminaires (open surface mount luminaires with compartment protection from weather)
- For use with Class 2 driver only



CoreTech LED Series

Specification Data

Model	Lamp Input Current	System Wattage	Lamp Wattage	Length	CRI	Initial Lumens	Lamp Efficacy (lm/W)	System Efficacy (lm/W)	Beam Angle	CCT
L36T8/935/11G-XT	250mA	12	9	36"	90	1400	155	116	325	3500K
L36T8/935/11G-XT	300mA	14	11	36"	90	1600	145	115	325	3500K
L36T8/935/11G-XT	360mA	15	13	36"	90	1900	158	127	325	3500K

Wiring Diagram



DLC Information

Order Code	Lamp Input Current	DLC Product ID	DLC Product Model	DLC Product Version
L36T8/935/11G-XT	250mA	N/A	N/A	N/A
L36T8/935/11G-XT	300mA	N/A	N/A	N/A
L36T8/935/11G-XT	360mA	PLL81B4	L36T8/935/11G-XT	5.1

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.