

Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rated
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- Driver Efficiency Greater than 85% at full power
- THD \leq 20% at full power
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Auto Recovery Short Circuit Protection, Over Load Protection, Over Voltage Protection
- Ambient Operating Temperature: -30 ~ 40°C
- Works in cold temperature applications
- 5 Year Warranty



Commercial Recessed Downlight



Specification Data

Model No.	Size	IC Rated	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Beam Angle (°)	Dimension
VEKR4D/8T/10W-10V	4" Recess	Yes	5 / 7 / 10	550 / 770 / 1100	3000K, 3500K, 4000K selectable	110	120-277	>80	0.9	100	Dia. 5.71" x Height 3.70"

Ordering Information

Sample model: VEKRD/ET10W-32V

Series	Size	BT	10W	20W
Series ES	ES	ES	ES	ES
Series Light	4"	T. 10W CCT	10W Max.	20W
Overlight	4"	2-Button	2-Button	2-Button



User Manual [468inDownlightInstallation.pdf](#)