

# CRI80

## Commercial Grade Recessed Downlight



### Product Certification

### Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rateds
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- Driver Efficiency Greater than 85% at full power
- THD  $\leq$  20% at full power
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Auto Recovery Short Circuit Protection, Over Load Protection, Over Voltage Protection
- Ambient Operating Temperature: -30 ~ 40°C
- Works in cold temperature applications
- Flicker-Free, Meets IEEE 1789-2015
- 5 Year Warranty

### Specification Data

Model No.	Size	IC Rated	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Beam Angle (°)	Dimension
VEKR6D/8T/13W-10V	6" Recess	Yes	6.5 / 9 / 13	790 / 1100 / 1560	3000K, 3500K, 4000K selectable	120	120-277	>80	0.9	100	Dia. 8.27" x Height 4.25"

### Order Information

EXAMPLE: VEKR4D/8T/10W-10V				
VEKR	4D	8T	10W	10V
<b>Series</b> Retrofit Kit Recessed Light	<b>Size</b> 4" Downlight	<b>CRI&gt;80 T: three CCT adjustable</b>	<b>Wattage</b> 10W Max.	<b>0-10V dimming</b>

### Image



User Manual [468inDownlightInstallation.pdf](#)