

CRI80

Commercial Grade Recessed Downlight



Product Certification

Features & Benefits

- Commercial Downlight Retrofit or New Construction
- Universal Voltage 120-277V
- UL for Safety, Wet-Location Rateds
- Three Adjustable Lumen Output
- Three Adjustable CCT Options (3000K, 3500K, 4000K)
- Driver Efficiency Greater than 85% at full power
- THD \leq 20% at full power
- High CRI
- Long Life
- Convenient and quick installation
- 0-10V Dimmable
- 25" Flexible Conduit
- Auto Recovery Short Circuit Protection, Over Load Protection, Over Voltage Protection
- Ambient Operating Temperature: -30 ~ 40°C
- Works in cold temperature applications
- Flicker-Free, Meets IEEE 1789-2015
- 5 Year Warranty

Specification Data

Model No.	Size	IC Rated	Watts	Lumens	CCT	Efficacy	Input Voltage	CRI	Power Factor	Beam Angle (°)	Dimension
VEKR9.5D/8T/27W-10V	9" Recess	Yes	17 / 21 / 27	2070 / 2500 / 3240	3000K, 3500K, 4000K selectable	120	120-277	>80	0.9	100	Dia. 11.22" x Height 5.04"

Order Information

EXAMPLE: VEKR4D/8T/10W-10V				
VEKR	4D	8T	10W	10V
Series Retrofit Kit Recessed Light	Size 4" Downlight	CRI>80 T: three CCT adjustable	Wattage 10W Max.	0-10V dimming

Image



User Manual [9.5inDownlightInstallation.pdf](#)