
LBS Lighting





DIMENSIONS



AT A GLANCE

STYLE
Colonial post top

CONSTRUCTION
Composite, fade & rust resistant

MOUNTING
Fits 3" diameter post

RATING
UL Listed, wet locations

VOLTAGE
120V

LAMPING
Dedicated LED or medium-base lamp

c UL us

BAA FIXTURE

QUESTIONS & ORDERS
sales@lightbulbsurplus.com

SPECIFICATION SHEET

FC234 Colonial Post

A traditional colonial lantern in fade- and rust-resistant composite. Order it with a dedicated 120V LED engine or as a medium-base incandescent fixture, in black or white, with a clear or frosted acrylic diffuser.

- Fade & rust resistant composite
- UL Listed for wet locations
- Fits 3" diameter post

HOW TO ORDER

Example: FC234-I60-BC-LWE

STYLE	LIGHT SOURCE	BODY	DIFFUSER	OPTIONS
FC234	**LE800 / I60**	**B / W**	**C / F**	**LWE / LCE**
Colonial post top	**LE800** Dedicated 120V LED, 13W **I60** Incandescent, medium base, 120V, 1 × 60W max	**B** Black **W** White	**C** Clear acrylic **F** Frost acrylic	**LWE** LED A19/E26 lamp, 90 CRI, 3000K **LCE** LED A19/E26 lamp, 80 CRI, 4000K I60 only; N/A with LE800

LIGHT SOURCE DETAIL

LE800 Dedicated 120V LED

Power	13W
CRI	80
Efficacy	> 88 lm/W**
W – 3000K	1,140 lm
C – 4000K	1,280 lm
Input	120V AC, 50/60 Hz, HPF
Life	50,000 hrs L70
Ambient temp.	-40°C to +40°C
Dimming	Dimmable
Warranty	5 years

EOS LED engine

I60 Incandescent 120V

Socket	Medium base
Voltage	120V
Max lamp	1 × 60W

OPTIONAL LED LAMP

LWE	A19/E26, 90 CRI, 3000K
LCE	A19/E26, 80 CRI, 4000K
Dimming	Dimmable
Warranty	3 years

Dimmer compatibility information available on request. Data per LM-79 / LM-80 / TM-21 available on request. **Estimated from LED source. Fixtures available with custom packaging options, assembled or knocked down; MOQs apply. Specifications subject to change without notice.

PROJECT	TYPE	CATALOG #	APPROVED BY